

Drainage Reports

Abbreviated Water & Sewer Need Reports

Water Study

Wastewater Study

Stormwater Waiver Application



Advanced Consulting & Engineering Solutions

PRELIMINARY DRAINAGE REPORT

For

Plan # _____ **Goldwater Development**

Case # 4-ZN-298

Q-S # _____

☒ Accepted

☐ Corrections

DG
Reviewed By

3/5/19
Date

C.O.S. CASE NO. 4-ZN-2018

This day of: February 2019

Engineer of Record:

Joseph Hassell P.E.



2/5/19

Ace Job #: 17-096

Prepared By:

Ace Solutions, LLC
609 N Calgary Ct. Ste. 7
Post Falls, ID 83854
208-777-1854

Prepared For:

Goldwater Boulevard, LLC
Robert Ballard
480-203-8661

Contents

| | |
|---|----|
| INTRODUCTION | 4 |
| Previous Drainage Studies or Master Plan | 4 |
| Location | 5 |
| Description of Property | 5 |
| Vicinity Map | 5 |
| General Project Description | 6 |
| Construction schedule | 6 |
| Applicant information | 6 |
| Engineer Information | 6 |
| STORMWATER DESIGN CRITERIA | 6 |
| Regulations: Preliminary Report | 6 |
| Analysis Methods | 7 |
| Hydrologic Criteria | 7 |
| Datum | 10 |
| STORM WATER MANAGEMENT PLAN | 10 |
| General Description | 10 |
| Hydrological Analysis | 11 |
| Hydraulic Analysis and Design | 12 |
| UNDERGROUND STORAGE TANK DESIGN | 13 |
| UNDERGROUND LEVEL DESIGNS | 16 |
| Erosion Control | 16 |
| Stormwater Pollution Prevention- General Permit | 17 |
| CONCLUSIONS | 17 |
| Warning and Disclaimer of Liability | 17 |
| References | 17 |

TABLES

| | |
|--|----|
| Table 1: Rainfall Depths..... | 12 |
| Table 2: Runoff Coefficients | 12 |
| Table 3: USST Summary..... | 12 |
| Table 4: Estimated Tank Drainage Times | 13 |

FIGURES

| | |
|--|----|
| Figure 1: Water Surface Elevation at 70th St. | 8 |
| Figure 2: Water Surface Elevation at 4th St. | 8 |
| Figure 3: Flow rate at 70th St. | 9 |
| Figure 4: Flow Rate at 4th St. | 9 |
| Figure 5: Flow Rate at new inlet..... | 10 |

LIST OF APPENDICES

- Appendix A: NOAA Atlas 14, Volume 1 - Precipitation Frequency
- Appendix B: Stormwater Calculations
- Appendix C: Floodplain data
- Appendix D: Plans
- Appendix E: Warning and Disclaimer of Liability

INTRODUCTION

This Storm Water Management report is being developed at the request of the City of Scottsdale to verify that runoff from the Goldwater Development site property under developed conditions will comply with the City's stormwater ordinance and its Design Standards and Policy Manual (DSPM). Site location is the corner of 70th and Goldwater Blvd. Old Town Scottsdale, Arizona. Total lot area is 1.19 Ac. The lot currently has a city owned 24-inch diameter stormwater drain from the end of 4th street to a storm drain manhole in Goldwater Boulevard.

The storm drain will need to be eliminated at 4th street. The stormwater will be designed to flow above ground along the southern property line. Near the east end of the property, the storm flow from the street will be captured in a new catch basin which will pipe the water back to the existing stormwater outlet located in Goldwater Blvd. The new area of pipe will need a drainage easement of 12 feet wide. We have planned to use 18-inch diameter storm drain piping.

In order to retain the stormwater from the developed site condition, an underground stormwater storage tank will be utilized. Per our calculations, 7750 cubic feet of storage is required. The tank will be located on the east end of the property. Catch basins around the property will drain to the tank location, where there will be an outfall pipe that drains to the city system at the maximum allowed rate of 1 cubic foot per second. The tank will be designed as such that a storm larger than the 100 year, 2-hour storm will result in excess water draining to a drywell on site. Drainage easements will be given where required at the storage tank and piping locations.

This submittal is considered preliminary not for construction. A final plan set and certifications will be submitted at a later date. The final submittal will reflect the current city code requirements.

Previous Drainage Studies or Master Plan

The city of Scottsdale has provided as built drawings of the stormwater system for the area and has notified us of a maximum discharge rate into the existing storm system of 1.0 cfs. The existing lot does not have any existing stormwater storage volume.

Location

The proposed development site contains approximately 1.19 acres located between Goldwater Boulevard and 4th Street, Scottsdale. Access to the property is from 4th Street.

Description of Property

The property is located between Goldwater Boulevard and 4th Street in Old Town Scottsdale, Arizona. Access to the property is from 4th Street. The property is currently undeveloped. All street front improvements are in place. The property owners have requested a 10 foot in width right of way abandonment adjacent to 4th Street. This right of way abandonment is not necessary for the drainage plan, it affects the layout of the building.

The property is currently zoned for commercial development.

This project is not near a floodplain area and there are no visible wetlands in the area. See attached FEMA map in appendix C for Scottsdale community number 045012.

Vicinity Map



General Project Description

The purpose of the proposed development is to construct a new 5 story residential condominium with parking in the basement and ground level. The project will also include grading, curb and gutter, paving, stormwater retention areas utilizing underground storage tanks, landscaping and sidewalks, building, parking, and relocation of the existing stormwater drains, pipes and easements.

Construction schedule

Construction is anticipated to begin in late summer of 2019. Construction will not be phased.

Applicant information

Owner: Goldwater Boulevard LLC

Contact: Bob Ballard

480-203-8661

Scottsdale, Arizona

Engineer Information

ACE Solutions LLC

Project Engineer: Joseph Hassell, PE

609 N. Calgary Ct. Ste. 7

Post Falls, Idaho 83854

Telephone: 208-777-1854

Email: joeh@acesolutions.pro

STORMWATER DESIGN CRITERIA

Regulations: Preliminary Report

City of Scottsdale 2018 DSPM was used for this report. A final report will use the current DSPM.

Analysis Methods

Our hydrological analysis is based on the Rational Method. This method utilizes rainfall frequencies and runoff characteristics from a watershed to predict peak discharges during storm events. This method is suitable for storm analysis on site 160 ac. or less. The storm event for 100-year frequency was analyzed. Storm event data was collected for the NOAA Atlas 14, volume 1 Version 5.0 of Western United States.

The analysis uses sheet flow across the surfaces for pre-developed conditions as well as post-developed conditions. Time of concentration was calculated using the existing and proposed surface runoff coefficients and the length of basin was from the further reaches on site to the average distance to the proposed detention area.


Hydrologic Criteria

At the requirement of the City of Scottsdale DSPM, hydrologic modeling was completed using the 100-year frequency rainfall events as reported in NOAA Atlas 14, Volume 1 Rainfall Frequency Atlas of the Western United States. This data is included in Appendix A. The runoff response from the 6-hour duration storm event was studied to look at historical drainage patterns. These patterns were studied to determine if runoff would enter or leave the property in its pre-development state. The information used was provided by the Lower Indian Bend Wash Area Drainage Master Study (LIBWADMS). Data from the study allows for us to draw a line at certain areas in order to determine the water surface elevation and the flow rates over time after the storm.

Generally, the study confirms the water will flow past the site and not on to the site. Along Goldwater, water will flow away from the property to the North East. Along 70th street, water generally follows the layout of the street. Logically, some water must continue down 4th street. Study shows the water here is lower than the curb height, and with the existing catch basin capturing water at 4th street there should be no water entering the site from the street. A map showing the water flow directions is provided in Appendix C.

Using data from the study, we can determine the water surface elevation at selected points. Our first study location was along 70th street just to the North of the intersection with 4th Street. The following figure shows the results. A full-size version of each of the following figures can be found in Appendix B.


Figure 1: Water Surface Elevation at 70th St.



It was determined that the maximum water surface elevation at this location is 0.53', or just over 6 inches. The curb height at this location is 6 inches, and the water generally runs to the south. Even if the curb were overtopped at this location, the water flow would lead it south along 70th street to the intersection with 4th street, which has more storage capacity for the flows exhibited.

The water surface elevation was also studied at the 4th street Cul-de-Sac. The following figure shows the results.


Figure 2: Water Surface Elevation at 4th St.



The maximum water surface elevation at this location is 0.47', just under 6 inches. With a 6-inch tall curb at this location, overtopping should not be a concern, especially with the existing catch basin in the Cul-de-Sac capturing stormwater into the city system.


We can also use data from the LIBWADMS to determine the flow rate for the 100-year, 6-hour storm. Figure 3 presents the flow rate over time from the same location studied in figure 1.

Figure 3: Flow rate at 70th St.



Using the information shown above, we determined that the maximum flow at 70th street was 54.31 cfs. This flow occurs 4 hours after the storm. Figure 4 presents information from the same location as figure 2.


Figure 4: Flow Rate at 4th St.



Using this information, it was determined that the maximum historical flow at the 4th street culvert inlet is 5.88 cfs. Since we are planning on removing this inlet, we must design for the same flow to be conveyed back to the city system. This calculation is presented in Appendix B, with the result shown on plan page C6 in Appendix D.

We also viewed the flow rate at the location where the new inlet will be placed. Had this rate been higher than shown in figure 4, we would use this higher rate.

Figure 5: Flow Rate at new inlet



The maximum flow at this location is 4.83 cfs. We will use the data from figure 4 to as the baseline for stormwater flows contained by the city system.

Datum

All elevations listed in this report refer to the NAVD-88 GEOID 09 datum. Upon final submittal We will provide equation and location for conversion to the City of Scottsdale datum and local bench mark.

STORM WATER MANAGEMENT PLAN

General Description

All stormwater runoff will be collected and piped to a detention vault which will outfall into the city storm system. The city will only allow 1.0 cfs discharge at any one time. A drywell will also

be designed to contain flows over the 100-year flood and to speed up outflow from the detention vault.

The proposed detention vault will be constructed to discharge runoff from the site at or below the allowed rate of 1.0 cfs, per the DSPM section 4-1.201. All stormwater will be collected and directed into the underground stormwater storage tank (USST). A Drywell is proposed to capture any overflow above the 100-year event. In the USST, two outflow pipes will be placed at minimum. The first will allow outflow to the city system at the proposed 1.0 cfs. This will be designed to always allow outflow as long as there is water in the USST. A second pipe will be designed above the required storage that allows for outflow to the drywell. The drywell will be sized later, but it is assumed that it will handle all the additional water of storms stronger than the 100-year, 2-hour storm.

The underground detention vault must be constructed to comply with the criteria in the 2018 Design Standards and Policy Manual (DSPM), Chapter 4, Section 4-1.202.

There is also a basement level to the building accessible via a ramp down to the level. This must include drains for the inevitable stormwater that will run down the ramp and water that will run off the cars parked there. Our basement level plan is shown on plan page C2 in Appendix D.

An existing 24-inch diameter storm drain line runs through a section of what will become the ramp down to the lower level. This drain line will be removed, and the easement abandoned to allow for the parking ramp installation. In its' place, a scupper will be installed further south to allow for sheet flow of the street stormwater past the sidewalk. A concrete spillway will be installed beneath the sidewalk and to the south of the parking lot allowing the water to flow past the parking lot. From there it will be conveyed in a v-ditch, lined with rip rap to prevent erosion. It will be directed north directly into a new catch basin, where it will be directed to the city system in a new storm drain. This is shown on plan page C6, included in appendix D. Drainage easements will be provided for the new storm drains. Additional drain pipe will need to be installed to re-route the line towards the existing city drain.

A recreational swimming pool is designed to be on site. The design of this pool is by other firms, but the drains and backwash systems must be connected to the sanitary sewer system.

Hydrological Analysis

For sites that have not been previously developed, the standard formula is shown below:

$$V_r = C(R/12)A$$

See City of Scottsdale DSPM for more information regarding this formula.

The provided spread sheet calculates a weighted "C" to apply over the entire site. All stormwater from the 100-year, 2-hour precipitation event must be contained on site.

Additional calculations are shown using data from NOAA Atlas 14, Volume 1 to determine historical flows for 2, 10, 25, and 100-year storms.

Table 1 provided below summarizes the rainfall amounts for each of the analyzed storm events.

Table 1: Rainfall Depths

| Rainfall Duration | 10-Year | 25-Year | 50-Year | 100-Year |
|-------------------|---------|---------|---------|----------|
| 2 Hour | 1.38" | 1.69" | 1.92" | 2.16" |

A weighted C factor has been calculated for each sub-basin based on the existing and developed conditions using coefficients from the DSPM. Table 2 gives runoff coefficients used to calculate the weighted C value for various land usages. We are considering that the current site can be labeled a gravel floodway and shoulder.

Table 2: Runoff Coefficients

| Land Cover | Specific/Composite | Storm Freq. (years) | | |
|---|-------------------------|---------------------|------|------|
| | | 2-25 | 50 | 100 |
| Lawns, golf courses & parks | Specific Surface Values | 0.20 | 0.25 | 0.30 |
| Paved Streets, Parking Lots, roofs, driveways, etc. | Specific Surface Value | 0.90 | 0.93 | 0.95 |
| Apartments & Condominiums | Composite Area Values | 0.76 | 0.83 | 0.94 |
| Gravel Floodways and Shoulders | Specific Surface Values | 0.68 | 0.78 | 0.82 |

Hydraulic Analysis and Design

Retention

Table 3 provided below summarizes the water surface elevations, inflow, outflow, depth and storage required within the proposed USST. The tank will be composed of multiple cells, which when combined hold a minimum of 7750 cf (100 yr.). The outfall weir allows a maximum of 1.0 cfs. Of outfall directly into the city system. Overflow will be directed into an onsite drywell.

Table 3: USST Summary

| Event | Max WSEL (ft.) AVG | Freeboard (ft.) At outfall | Max Q_{in} (cfs) | Max Q_{out} (cfs) | Depth(ft.) | Storage Requirement (cft.) |
|---------|-----------------------|-------------------------------|--------------------|---------------------|------------|----------------------------|
| 10-Year | TBD | 3.62 | 1.26 | 1.0 | 3.88 | 4544 |

| | | | | | | |
|----------|-----|------|------|-----|------|------|
| 25-Year | TBD | 2.74 | 1.54 | 1.0 | 4.76 | 5565 |
| 100-Year | TBD | 0.88 | 2.12 | 1.0 | 6.62 | 7750 |

WSEL= Water Surface Elevation from bottom of vault at outfall location for indicated storm event

Retention will be provided to control developed runoff release to rates as allowed by the city (1.0 cfs). The Existing Conditions have a greater discharge then allowed. Freeboard will be provided during all analyzed storm events. However, if overtopping were to occur, overflow from the detention vault will be piped to an area drywell. Drywell to be sized at a later date.

UNDERGROUND STORAGE TANK DESIGN

According to the above calculations, a minimum of 7750 cubic feet of storage is required in the USST. As shown on plan page C6 in appendix D, we have designed a trapezoidal tank totaling 1170 square feet in surface area. The total tank will be 7.5' deep to allow for sediment buildup. If we design for 7 feet of storage, the tank should be able to hold 8190 cubic feet of water.

In our current design, we must outflow to the city approximately 6.5' below grade. This leaves 1 foot of water in the tank that must be removed.

The outfall pipe to the city system will be placed near the bottom of the tank, approximately 6 inches from the bottom to allow for sediment to settle. An outfall pipe will be placed within 12 inches of the top of the tank which will outflow to the drywell. The basic design is shown on plan page D1 in Appendix D.

Table 4: Estimated Tank Drainage Times

| Outlet Height (from Base) | Outlet Flow rate (cfs) | Volume Drained by outlet (cu. Ft) | Total Drainage Time (hrs.) |
|------------------------------|------------------------|---|-------------------------------|
| 0'-0.5' | 0.1 (drywell) | 1755 | 5 |
| 1.5' | 1.0 (city system) | 6435 | 1.8 |
| 6.5-7.0' (TBD) | TBD | TBD | TBD |

Table 4 shows the estimated time to drain the tank at full capacity. By adding the results of the last column, we can see that the tank will drain in less than 7 hours.

Comparing the data in Table 4 with the historical flows shown in Figure 4, we see after the 100-Year, 2-hour storm, the tank will empty before off-site stormwater is conveyed through the site. The 4-hour delay shown in Figure 4 will help us to make sure that the city stormwater system is not overloaded when dealing with our outflow and the historical outflow.

Per the DSPM Chapter 4, Section 4-1.202 the storage tank must meet the following criteria, with comments following showing how we plan to meet the criteria:

C. GENERAL CRITERIA FOR UNDERGROUND STORMWATER STORAGE SYSTEM DESIGN

1. Underground stormwater storage systems must demonstrate protection of public health, safety, and welfare as established by the SRC and related policies.

The final design will incorporate these aspects.

2. Storage systems must not be located under structures, parking garages, or significant landscaping such as trees or sizable cactus that would preclude access to or replacement of the facilities.

Please see attached plan pages in Appendix D for storage location. The location shown meets these criteria. We have removed the fence previously shown on drawings to accommodate the tank location shown.

3. The owner must dedicate a public drainage easement to the city which meets the standards for all drainage easements.

This will be comped prior to construction completion. The easement is shown on plan page C6 in Appendix D.

4. Design must address:

- a. Water quality protection measures to protect underground and surface water resources to meet applicable water quality standards.
- b. Vector control within storage system.
- c. Redundancy in case of storage system failure, with attention to the possibility of structure or street flooding, sediment accumulation, or storm events that are greater than the 100-year, 2-hour event.
- d. Initial suspended sediment load removal.
- e. At least a 75-year life of entire system, including the lining and coating of the underground storage tank.
- f. Drainage by gravity. Pumped systems will only be considered if no other reasonable alternative exists with dry wells as a preferred alternative if drainage by gravity is not feasible.

These points will be addressed as part of the final design. We anticipate that the storage system will be able to drain to the adjacent drywell and to the city system via the outflow piping. If the structure should become overtopped, overflow will be piped to an adjacent drywell. As shown in previous paragraphs, we cannot empty the tank completely using the city system and will drain the remainder to a drywell. This will be done via gravity.

D. SPECIFIC CRITERIA FOR UNDERGROUND STORMWATER STORAGE DESIGN

1. Outfall—underground storage systems must have some sort of outfall, such as gravity drains or pumps.

See above notes. The structure will outflow via outflow piping.

2. Pipes—underground storage system pipes must have a smooth interior floor. The city's Maricopa Association of Governments (MAG) supplemental standard detail 2554 shall be used to meet the smooth interior floor requirement for the use of corrugated metal pipes in underground stormwater storage facilities.

These types of pipes will be used.

3. Installation—excavation, bedding, and backfill procedures and materials must be in accordance with MAG standards.

These standards will be followed.

4. Access—a minimum of two access points must be provided for each underground storage system unless waived in advance by stormwater staff to enable inspections and access for removal of accumulated sediment and debris. Access must be in accordance with MAG standards and be placed to maximize the ability to maintain the underground system.

The final detention vault design will follow these standards.

E. CRITERIA FOR OPERATIONS, MAINTENANCE AND LIABILITY

1. Operations and maintenance generally—owner must provide:

- a. Maintenance staff with expertise in operating, inspecting, and maintaining an underground stormwater storage system;
- b. An Operations and Maintenance Manual on site for the system that includes:
 - i. a schedule for inspections and maintenance, and
 - ii. provisions for emergency operations due to power failure, pump failure, and clogged outlet structures;
 - iii. A log of the inspections and required maintenance services.

We will insure the owner provides this information.

2. Inspections and maintenance required—In addition to maintenance required by the SRC and other applicable requirements, owner shall:

- a. Inspect system after each storm event of 0.6 inch or more, and semiannually, preferably before summer and winter rains.
- b. Remove accumulated trash and debris from inlet and outlet structures as needed to ensure free flow of stormwater.
- c. Inspect all other elements of the drainage system (pipes, geotextiles, and stone) and repair/replace elements as needed for the storage system to operate at peak efficiency.

The owner will provide this.

3. Signage—before receiving a C of O, the owner must install signs at each end of the underground storage tank that read "Notice—Underground Stormwater Storage Tank." The size, color, and locations of signs are subject to city staff approval.

This will be provided.

4. Ownership Responsibility Statement – The owner shall provide and sign a statement of responsibility for the system stating and acknowledging the owner is responsible for the maintenance, repair, and potential replacement of the system. Prior to final plan approval, the

owner must provide a signed and notarized document to this effect, in a form satisfactory to the City Attorney, for recordation by the city in the Maricopa County Recorder's Office.

This will be provided.

UNDERGROUND LEVEL DESIGNS

The Underground level must be accounted for in the stormwater design. There is one level underground, accessible from a ramp that meets the existing cul-de-sac. An existing storm pipe runs through this area and will have to be moved.

The ramp to the lower level will have a roof over preventing most of the rainwater from running down the ramp. Also, there will be a small rise in elevation from the cul-de-sac trapping water from the street from getting to the ramp. At the top of this rise we will place a grate drain across all lanes of traffic to catch most water that may try to overflow into the basement level.

At the bottom of the ramp a grate drain will be placed across all lanes of traffic. Catch Basins will be placed within the parking area and the parking sloped slightly to drain the water towards the basins. All the water from the drain and from the basins will be conveyed to a sump pump location. From there the water will be pumped up to the surface level where it will drain to the underground storage tank.

Erosion Control

Description

Construction of the project shall include erosion and sediment control. Perimeter erosion controls shall be installed prior to any soil disturbance on site. Interior erosion controls shall be installed after rough grading. The contractor shall install additional erosion control measures as need and shall be responsible for installing and maintaining all erosion control measures. The owner is responsible for erosion control for all contractors working on the site, including minimizing tracking of soil and debris onto adjacent properties and roadways and wind erosion control.

Areas not being developed or planned to be developed for a period of greater than 14 days shall be stabilized to minimize wind and water erosion. This includes periods of winter shut down. Wind erosion protection shall be accomplished by mulching/crimping until 70% vegetation is established. Permanent erosion control shall be achieved by permanent seeding of slopes, disturbed ditch sections and disturbed pond areas. The seed mix shall be a sustainable perennial variety. Further, the contractor is responsible for all clean-up resulting from site erosion and soil tracking. Tracking must be removed by the end of each work day. Erosion control structures shall be in place prior to any land-disturbing activities. Maintaining erosion control structures, site clean-up, and re-evaluation of the erosion plan shall be done on a regular basis, particularly after any storm water event.

See attached development plans for graphical representation of the erosion control plan.

Stormwater Pollution Prevention- General Permit

If the project requires that a General Permit be obtained by the Arizona State Department of Ecology or EPA, an application package with all related and subsequent requirements may be acquired by contacting the Engineer of Record. The forms and requirements outline in the package are also available on the Scottsdale City website.

CONCLUSIONS

Runoff from developed conditions was compared against the runoff rates modeled for existing conditions. The analysis shows that, with the addition of the proposed detention vault, runoff from all analyzed areas under developed conditions, will be retained during the analyzed storm events when compared to existing conditions. The property outfall location will remain the same.

Warning and Disclaimer of Liability

For this preliminary, conceptual, design we have shown that is feasible to control the stormwater runoff on site and meet the city requirements for discharge into their system. We do not recommend the stormwater facilities be built without further engineering and design and full approval from the city.

A signed warning and disclaimer of liability is included in Appendix E

References

The site plan has been analyzed using Atlas 14, volume 1 rainfall rates and soils information provided by onsite inspection. The City of Scottsdale 2018 DSPM has been used for this submittal.

Please feel free to contact Joe Hassell P.E., or Nick Ebner EIT at 208-777-1854 with any questions or comments regarding this SWMP.



NOAA Atlas 14, Volume 1, Version 5
 Location name: Scottsdale, Arizona, USA*
 Latitude: 33.4897°, Longitude: -111.9299°
 Elevation: 1253.07 ft**
 * source: ESRI Maps
 ** source: USGS



POINT PRECIPITATION FREQUENCY ESTIMATES

Sanja Perica, Sarah Dietz, Sarah Heim, Lillian Hiner, Kazungu Maitaria, Deborah Martin, Sandra Pavlovic, Ishani Roy, Carl Trypaluk, Dale Unruh, Fenglin Yan, Michael Yekta, Tan Zhao, Geoffrey Bonnin, Daniel Brewer, Li-Chuan Chen, Tye Parzybok, John Yarchoan

NOAA, National Weather Service, Silver Spring, Maryland

[PF tabular](#) | [PF graphical](#) | [Maps & aeries](#)

PF tabular





| PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches) ¹ | | | | | | | | | | |
|--|-------------------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-----------------------|
| Duration | Average recurrence interval (years) | | | | | | | | | |
| | 1 | 2 | 5 | 10 | 25 | 50 | 100 | 200 | 500 | 1000 |
| 5-min | 0.183 (0.154-0.223) | 0.240 (0.202-0.291) | 0.326 (0.273-0.395) | 0.392 (0.326-0.472) | 0.481 (0.394-0.577) | 0.550 (0.444-0.657) | 0.620 (0.492-0.739) | 0.692 (0.540-0.824) | 0.788 (0.598-0.940) | 0.862 (0.641-1.03) |
| 10-min | 0.279 (0.234-0.339) | 0.364 (0.307-0.443) | 0.495 (0.415-0.600) | 0.596 (0.496-0.719) | 0.732 (0.599-0.878) | 0.837 (0.676-1.00) | 0.944 (0.748-1.12) | 1.05 (0.821-1.25) | 1.20 (0.911-1.43) | 1.31 (0.976-1.57) |
| 15-min | 0.345 (0.290-0.420) | 0.452 (0.381-0.549) | 0.614 (0.514-0.744) | 0.739 (0.614-0.891) | 0.907 (0.743-1.09) | 1.04 (0.838-1.24) | 1.17 (0.928-1.39) | 1.31 (1.02-1.55) | 1.49 (1.13-1.77) | 1.63 (1.21-1.94) |
| 30-min | 0.465 (0.390-0.565) | 0.608 (0.513-0.740) | 0.827 (0.692-1.00) | 0.995 (0.827-1.20) | 1.22 (1.00-1.47) | 1.40 (1.13-1.67) | 1.58 (1.25-1.88) | 1.76 (1.37-2.09) | 2.00 (1.52-2.39) | 2.19 (1.63-2.61) |
| 60-min | 0.575 (0.483-0.700) | 0.753 (0.635-0.915) | 1.02 (0.857-1.24) | 1.23 (1.02-1.49) | 1.51 (1.24-1.82) | 1.73 (1.40-2.07) | 1.95 (1.55-2.32) | 2.18 (1.70-2.59) | 2.48 (1.88-2.95) | 2.71 (2.02-3.24) |
| 2-hr | 0.666 (0.569-0.795) | 0.863 (0.736-1.03) | 1.16 (0.983-1.37) | 1.38 (1.16-1.64) | 1.69 (1.40-1.99) | 1.92 (1.57-2.26) | 2.16 (1.75-2.54) | 2.41 (1.91-2.82) | 2.74 (2.12-3.21) | 2.99 (2.27-3.54) |
| 3-hr | 0.724 (0.614-0.870) | 0.929 (0.793-1.12) | 1.22 (1.04-1.47) | 1.45 (1.22-1.74) | 1.78 (1.47-2.11) | 2.04 (1.66-2.41) | 2.31 (1.85-2.73) | 2.59 (2.04-3.06) | 2.98 (2.28-3.52) | 3.29 (2.46-3.91) |
| 6-hr | 0.873 (0.756-1.03) | 1.11 (0.962-1.30) | 1.42 (1.23-1.66) | 1.67 (1.43-1.95) | 2.01 (1.70-2.33) | 2.28 (1.90-2.63) | 2.56 (2.10-2.95) | 2.84 (2.28-3.28) | 3.23 (2.53-3.74) | 3.53 (2.71-4.11) |
| 12-hr | 0.977 (0.855-1.13) | 1.23 (1.08-1.44) | 1.57 (1.36-1.81) | 1.82 (1.58-2.11) | 2.17 (1.86-2.50) | 2.44 (2.07-2.81) | 2.72 (2.27-3.13) | 3.00 (2.47-3.45) | 3.37 (2.71-3.91) | 3.67 (2.89-4.28) |
| 24-hr | 1.17 (1.05-1.32) | 1.49 (1.33-1.68) | 1.93 (1.72-2.18) | 2.28 (2.02-2.56) | 2.76 (2.43-3.11) | 3.14 (2.75-3.53) | 3.54 (3.08-3.97) | 3.95 (3.41-4.44) | 4.53 (3.86-5.08) | 4.98 (4.20-5.60) |
| 2-day | 1.26 (1.13-1.43) | 1.62 (1.44-1.82) | 2.12 (1.89-2.39) | 2.53 (2.24-2.84) | 3.09 (2.73-3.47) | 3.54 (3.11-3.98) | 4.02 (3.50-4.52) | 4.51 (3.90-5.08) | 5.21 (4.45-5.87) | 5.76 (4.88-6.51) |
| 3-day | 1.34 (1.19-1.51) | 1.71 (1.52-1.93) | 2.25 (2.00-2.53) | 2.69 (2.38-3.02) | 3.30 (2.91-3.70) | 3.79 (3.32-4.25) | 4.32 (3.75-4.84) | 4.87 (4.20-5.47) | 5.64 (4.80-6.34) | 6.26 (5.28-7.06) |
| 4-day | 1.41 (1.25-1.59) | 1.80 (1.60-2.04) | 2.38 (2.11-2.68) | 2.85 (2.52-3.20) | 3.51 (3.08-3.94) | 4.04 (3.53-4.53) | 4.61 (4.00-5.17) | 5.22 (4.49-5.86) | 6.07 (5.16-6.82) | 6.77 (5.69-7.61) |
| 7-day | 1.57 (1.39-1.77) | 2.00 (1.78-2.26) | 2.64 (2.34-2.98) | 3.16 (2.80-3.56) | 3.90 (3.43-4.38) | 4.49 (3.92-5.04) | 5.12 (4.44-5.75) | 5.79 (4.98-6.51) | 6.73 (5.72-7.57) | 7.49 (6.30-8.45) |
| 10-day | 1.70 (1.51-1.92) | 2.18 (1.94-2.45) | 2.87 (2.55-3.23) | 3.44 (3.04-3.86) | 4.22 (3.71-4.73) | 4.85 (4.24-5.43) | 5.52 (4.79-6.18) | 6.22 (5.36-6.98) | 7.21 (6.14-8.08) | 8.00 (6.74-8.99) |
| 20-day | 2.09 (1.87-2.34) | 2.69 (2.40-3.01) | 3.55 (3.17-3.97) | 4.20 (3.74-4.69) | 5.08 (4.50-5.67) | 5.76 (5.08-6.42) | 6.44 (5.65-7.19) | 7.14 (6.23-7.98) | 8.08 (6.99-9.05) | 8.81 (7.56-9.88) |
| 30-day | 2.44 (2.17-2.74) | 3.14 (2.80-3.52) | 4.14 (3.68-4.63) | 4.90 (4.35-5.47) | 5.92 (5.23-6.60) | 6.70 (5.89-7.47) | 7.51 (6.57-8.36) | 8.32 (7.25-9.27) | 9.42 (8.14-10.5) | 10.3 (8.81-11.5) |
| 45-day | 2.83 (2.53-3.16) | 3.64 (3.26-4.07) | 4.80 (4.29-5.36) | 5.66 (5.04-6.32) | 6.78 (6.02-7.57) | 7.63 (6.76-8.52) | 8.49 (7.49-9.49) | 9.35 (8.21-10.5) | 10.5 (9.13-11.8) | 11.3 (9.82-12.7) |
| 60-day | 3.13 (2.81-3.49) | 4.04 (3.63-4.51) | 5.32 (4.76-5.92) | 6.24 (5.58-6.95) | 7.45 (6.64-8.29) | 8.34 (7.41-9.29) | 9.24 (8.17-10.3) | 10.1 (8.91-11.3) | 11.3 (9.87-12.6) | 12.1 (10.6-13.6) |

¹ Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS). Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values. Please refer to NOAA Atlas 14 document for more information.

[Back to Top](#)

PF graphical**PDS-based depth-duration-frequency (DDF) curves**

Latitude: 33.4897°, Longitude: -111.9299°



NOAA Atlas 14, Volume 1, Version 5

Created (GMT): Fri Nov 2 16:49:47 2018

[Back to Top](#)**Maps & aerals**

Small scale terrain

Precipitation Frequency Data Server



Large scale terrain



Large scale map



Large scale aerial

11/2/2018

Precipitation Frequency Data Server



[Back to Top](#)

[US Department of Commerce](#)
[National Oceanic and Atmospheric Administration](#)
[National Weather Service](#)
[National Water Center](#)
1325 East West Highway
Silver Spring, MD 20910
Questions?: HDSC.Questions@noaa.gov

[Disclaimer](#)

Calculation Description

Objective: Determine the channel design required to convey the 100-year, 6-hour storm flows.

Method of Analysis: Data provided by the Lower Indian Bend Wash Area Drainage Master Study indicated that the maximum flow is 5.88 cfs at the 4th St. Cul-de-sac. We will use hydraulic study and the manning formula to determine flow.

Results:

It was determined that with the constraints given by the site geometry and the City of Scottsdale's requirements, two types of conveyances will work best. The first type will be constrained by the curb of the parking lot and a second curb constructed on the property line. The resulting rectangular shaped ditch will be about 40 inches wide. A shallow V-ditch will be installed after the parking lot to continue conveying water. Both conveyances will be lined with rip-rap to prevent erosion due to the relatively high flows

Conclusion:

The rectangular ditch needs to be 8 inches deep to convey the flow required. We will use a 10-inch-deep ditch in order to better convey flow higher than the maximum required. At the end of the parking lot, a V-ditch will convey the water back to a catch basin where it will flow to the city storm water system. This ditch will be 6 feet wide at the top, and 8 inches deep. It will slope 1% along its length. This will allow for a maximum flow of 6.15 cfs.

Ace Solutions

Open Channel Flow

| Description | Width (ft) | Depth (ft) | Slope (ft/ft) | Entrance Loss coefficient (K_e) | Mannings n | Area(ft ²) | Wetted Perimeter (ft) | Flow (ft ³ /sec) | Velocity (ft/sec) |
|-------------------------|---------------|------------|---------------|--|------------|------------------------|-----------------------------|--------------------------------|----------------------|
| V-Ditch Sheet Flow | 6 | 0.75 | 0.01 | 0 | 0.03 | 2.25 | 6.08 | 6.154 | 2.73 |
| Rectangle Shape at curb | 3.33 | 0.67 | 0.01 | 0 | 0.03 | 2.23 | 4.67 | 7.114 | 3.19 |

2/21

Calculation Description

Objective: Determine the historical flow rate for the 2 year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank. Also we plan to use the city's equation to determine the storage required for the 2-year storm. See the last calculation for additional details on the city's equation.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 2-year rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 2-year, 2-hour storm, the pre-developed outflow is 0.73 cfs and post-developed outflow is 0.78 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2.

Using the city equation, we find that 2842 cubic feet of storage is required for the 2-year, 2 hour storm.

The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations.

4/21

Entire building area basin 1

Preliminary

2-Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.68 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 0.86 |
| Pre-Developed Outflow (c.f.s.) | 0.73 |

Developed Condition

| | |
|--------------------------------------|------|
| Design Storm Intensity (2hr) (in/hr) | 0.86 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 2.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.73 |
| Area x "C" | 0.91 |
| Soil infiltration rate (in/hr) | 0.00 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft ³) (see below) | #6 V _{out} (ft ³) | Required Storage Volume (ft ³) |
|---------------------------|--|------------------------------|---------------------------------|--|--|---|
| 0 | | | | | | |
| 5 | 300 | 2.88 | 2.61 | 955 | 0 | 955.32 |
| 10 | 600 | 2.18 | 1.98 | 1319 | 0 | 1318.77 |
| 15 | 900 | 1.81 | 1.64 | 1584 | 0 | 1583.73 |
| 20 | 1200 | 1.61 | 1.46 | 1849 | 0 | 1849.17 |
| 25 | 1500 | 1.41 | 1.28 | 2007 | 0 | 2007.22 |
| 30 | 1800 | 1.22 | 1.10 | 2058 | 0 | 2057.87 |
| 35 | 2100 | 1.14 | 1.03 | 2237 | 0 | 2237.18 |
| 40 | 2400 | 1.06 | 0.96 | 2374 | 0 | 2374.50 |
| 45 | 2700 | 0.98 | 0.89 | 2470 | 0 | 2469.81 |
| 50 | 3000 | 0.91 | 0.82 | 2523 | 0 | 2523.13 |
| 55 | 3300 | 0.83 | 0.75 | 2534 | 0 | 2534.45 |
| 60 | 3600 | 0.75 | 0.68 | 2504 | 0 | 2503.78 |
| 120 | 7200 | 0.43 | 0.39 | 2844 | 0 | 2843.83 |

2843.83

$$(1) V_{in} = 1.34 * Q_{dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{dev} * t) + (.34 * Q_{dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|-------------------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.68 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.68 |

CN values not used with the rational method

Post-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.9 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.9 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.2 |
| Gravel | 0.00 | 0.00 | 76 | 0.55 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.73 |

Impervious Area:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation:

$$V_r = C(R/12)A$$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | | |
|--|------|------------------------|
| Pre-Developed Flow (cfs) | 0.73 | } Capacity is Adequate |
| Post-Developed Flow (cfs) | 0.00 | |
| Required Storage Volume (ft ³) | 2842 | |
| Storage Volume (ft ³) | 7750 | |

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

Calculation Description

Objective: Determine the historical flow rate for the 10-year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank. Also we plan to use the city's equation to determine the storage required for the 10-year storm. See the last calculation for additional details on the city's equation.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 10-year rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 10-year, 2-hour storm, the pre-developed outflow is 1.16 cfs and post-developed outflow is 1.26 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2.

Using the city equation, we find that 4544 cubic feet of storage is required for the 10-year, 2 hour storm.

The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations.

Entire building area basin 1

Preliminary

10-Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.68 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 1.38 |
| Pre-Developed Outflow (c.f.s.) | 1.16 |

Developed Condition

| | |
|--------------------------------------|-------|
| Design Storm Intensity (2hr) (in/hr) | 1.38 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 10.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.73 |
| Area x "C" | 0.91 |
| Soil infiltration rate (in/hr) | 0.00 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft³) (see below) | #6 V _{out} (ft³) | Required Storage Volume (ft³) |
|---------------------------|--|------------------------------|---------------------------------|---|---------------------------------|--|
| 0 | | | | | | |
| 5 | 300 | 4.70 | 4.27 | 1560 | 0 | 1560.35 |
| 10 | 600 | 3.58 | 3.24 | 2159 | 0 | 2159.30 |
| 15 | 900 | 2.96 | 2.68 | 2589 | 0 | 2589.32 |
| 20 | 1200 | 2.63 | 2.39 | 3024 | 0 | 3024.04 |
| 25 | 1500 | 2.31 | 2.10 | 3284 | 0 | 3283.51 |
| 30 | 1800 | 1.99 | 1.81 | 3368 | 0 | 3367.73 |
| 35 | 2100 | 1.86 | 1.69 | 3660 | 0 | 3660.43 |
| 40 | 2400 | 1.74 | 1.58 | 3884 | 0 | 3884.19 |
| 45 | 2700 | 1.61 | 1.46 | 4039 | 0 | 4039.01 |
| 50 | 3000 | 1.48 | 1.35 | 4125 | 0 | 4124.89 |
| 55 | 3300 | 1.36 | 1.23 | 4142 | 0 | 4141.83 |
| 60 | 3600 | 1.23 | 1.12 | 4090 | 0 | 4089.84 |
| 120 | 7200 | 0.69 | 0.63 | 4547 | 0 | 4547.49 |

4547.49

$$(1) V_{in} = 1.34 * Q_{dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{dev} * t) + (.34 * Q_{dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.68 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.68 |

CN values not used with the rational method

Post-Development:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.9 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.9 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.2 |
| Gravel | 0.00 | 0.00 | 76 | 0.55 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.73 |

Impervious Area:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation:

$$V_r = C(R/12)A$$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | |
|--|------|
| Pre-Developed Flow (cfs) | 1.16 |
| Post-Developed Flow (cfs) | 0.00 |
| Required Storage Volume (ft ³) | 4544 |
| Storage Volume (ft ³) | 7750 |

} Capacity is Adequate

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

9/21

Calculation Description

Objective: Determine the historical flow rate for the 25 year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank. Also we plan to use the city's equation to determine the storage required for the 25-year storm. See the last calculation for additional details on the city's equation.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 25-year rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 25-year, 2 hour storm, the pre-developed outflow is 1.42 cfs and post-developed outflow is 1.54 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2.

Using the city equation, we find that 5565 cubic feet of storage is required for the 25-year, 2 hour storm.

The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations.

Entire building area basin 1

Preliminary

25-Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.68 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 1.69 |
| Pre-Developed Outflow (c.f.s.) | 1.42 |

Developed Condition

| | |
|--------------------------------------|-------|
| Design Storm Intensity (2hr) (in/hr) | 1.69 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 25.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.73 |
| Area x "C" | 0.91 |
| Soil infiltration rate (in/hr) | 0.04 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft³) (see below) | #6 V _{out} (ft³) | Required Storage Volume (ft³) |
|---------------------------|--|------------------------------|---------------------------------|---|---------------------------------|--|
| 0 | | | | | | |
| 5 | 300 | 5.77 | 5.24 | 1915 | 0 | 1914.62 |
| 10 | 600 | 4.39 | 3.98 | 2652 | 0 | 2652.03 |
| 15 | 900 | 3.63 | 3.29 | 3178 | 0 | 3177.97 |
| 20 | 1200 | 3.23 | 2.93 | 3711 | 0 | 3710.59 |
| 25 | 1500 | 2.84 | 2.57 | 4028 | 0 | 4027.70 |
| 30 | 1800 | 2.44 | 2.21 | 4129 | 0 | 4129.28 |
| 35 | 2100 | 2.29 | 2.07 | 4489 | 0 | 4488.77 |
| 40 | 2400 | 2.13 | 1.93 | 4764 | 0 | 4763.91 |
| 45 | 2700 | 1.98 | 1.79 | 4955 | 0 | 4954.68 |
| 50 | 3000 | 1.82 | 1.65 | 5061 | 0 | 5061.10 |
| 55 | 3300 | 1.67 | 1.51 | 5083 | 0 | 5083.16 |
| 60 | 3600 | 1.51 | 1.37 | 5021 | 0 | 5020.86 |
| 120 | 7200 | 0.85 | 0.77 | 5569 | 0 | 5569.02 |

5569.02

$$(1) -V_{in} = 1.34 * Q_{dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{dev} * t) + (.34 * Q_{dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.68 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.68 |

CN values not used with the rational method

Post-Development:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.9 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.9 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.2 |
| Gravel | 0.00 | 0.00 | 76 | 0.55 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.73 |

Impervious Area:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation: $V_r = C(R/12)A$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | | |
|--|------|------------------------|
| Pre-Developed Flow (cfs) | 1.42 | } Capacity is Adequate |
| Post-Developed Flow (cfs) | 0.00 | |
| Required Storage Volume (ft ³) | 5565 | |
| Storage Volume (ft ³) | 7750 | |

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

12/21

Calculation Description

Objective: Determine the historical flow rate for the 100 year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 100-year, rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 100-year, 2-hour storm, the pre-developed outflow is 2.19 cfs, with post-development outflow at 2.12 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2. This The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations. An interesting conclusion is that using this method, we end up with a similar required storage as the city's equation (see next set of calculations). 7718 cubic feet vs. 7712 cubic feet.

Entire building area basin 1

Preliminary

One Hundred Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.82 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 2.16 |
| Pre-Developed Outflow (c.f.s.) | 2.19 |

Developed Condition

| | |
|--------------------------------------|--------|
| Design Storm Intensity (2hr) (in/hr) | 2.16 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 100.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.80 |
| Area x "C" | 0.98 |
| Soil infiltration rate (in/hr) | 0.04 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft³) (see below) | #6 V _{out} (ft³) | Required Storage Volume (ft³) |
|---------------------------|--|------------------------------|---------------------------------|---|---------------------------------|--|
| 0 | | | | | | |
| 5 | 300 | 7.44 | 7.32 | 2676 | 0 | 2676.03 |
| 10 | 600 | 5.66 | 5.57 | 3709 | 0 | 3708.53 |
| 15 | 900 | 4.68 | 4.60 | 4445 | 0 | 4445.19 |
| 20 | 1200 | 4.17 | 4.10 | 5195 | 0 | 5195.38 |
| 25 | 1500 | 3.67 | 3.61 | 5647 | 0 | 5646.57 |
| 30 | 1800 | 3.16 | 3.11 | 5799 | 0 | 5798.75 |
| 35 | 2100 | 2.96 | 2.91 | 6302 | 0 | 6301.60 |
| 40 | 2400 | 2.76 | 2.71 | 6685 | 0 | 6685.45 |
| 45 | 2700 | 2.56 | 2.51 | 6950 | 0 | 6950.28 |
| 50 | 3000 | 2.35 | 2.31 | 7096 | 0 | 7096.10 |
| 55 | 3300 | 2.15 | 2.12 | 7123 | 0 | 7122.90 |
| 60 | 3600 | 1.95 | 1.92 | 7031 | 0 | 7030.69 |
| 120 | 7200 | 1.08 | 1.06 | 7718 | 0 | 7718.07 |

$$(1) V_{in} = 1.34 * Q_{dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{dev} * t) + (.34 * Q_{dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.82 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.82 |

CN values not used with the rational method

Post-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.95 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.95 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.3 |
| Gravel | 0.00 | 0.00 | 76 | 0.82 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.80 |

Impervious Area:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation:

$$V_r = C(R/12)A$$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | | |
|--|------|------------------------|
| Pre-Developed Flow (cfs) | 2.19 | } Capacity is Adequate |
| Post-Developed Flow (cfs) | 0.00 | |
| Required Storage Volume (ft ³) | 7712 | |
| Storage Volume (ft ³) | 7750 | |

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

Calculation Description

Objective: Determine the required storage volume for the site

Method of Analysis: Equation provided by the City of Scottsdale Design Standards & Policies Manual (DSPM) Chapter 4, Section 1.201.C.

$$Vr = C \left(\frac{R}{12} \right) A$$

See referenced chapter for definition of terms.

Results:

Using data from the NOAA website, the depth in inches of the 100-year, 2-hour rainfall for this site is 2.16 inches. This is the "R" value. The weighted average runoff coefficient, "C" is found to be 0.80 this is shown in the table "Post-Development Tributary Area". This table also shows the "A" value.

Conclusion:

Using the equation above, we find that 7712 cubic feet of storage area is required. We plan to provide a minimum of 7750 cubic feet of storage. The objective is satisfied.

Entire building area basin 1

Preliminary

One Hundred Year Storm Event

DSPM Chapter 4, Section -1.201.C. Storage facilities volume

Pre-Developed Condition

| | |
|--------------------------------|--------|
| Area (square feet) | 53,852 |
| Pre-Developed "C" Factor | 0.82 |
| Design Storm Intensity (in/hr) | 2.16 |
| Pre-Developed Outflow (c.f.s.) | 2.19 |
| Time Increment (min) | 11.11 |

Developed Condition

| | | |
|--------------------------------|--------|---|
| Time Increment (min) | 2 hr | R |
| Design Storm Intensity (in/hr) | 2.16 | |
| Post-Developed Outflow (cfs) | 0.00 | |
| Design Year Flow (yr) | 100.00 | A |
| Area (sq. ft) | 53,852 | |
| Developed "C" Factor | 0.80 | |
| Soil infiltration rate (in/hr) | 0.00 | C |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

Storm Attenuation:

$$V_r = C(R/12)A$$

| | |
|--|------|
| Required Storage Volume (ft ³) | 7712 |
| Storage Volume (ft ³) | 7750 |

} Capacity is Adequate

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event


Post-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2886 | 0.07 | 98 | 0.95 |
| Buildings/atrium | 38174 | 0.88 | 98 | 0.95 |
| Grass/Lawn | 12792 | 0.29 | 50 | 0.3 |
| Gravel | 0 | 0.00 | 76 | 0.82 |
| 0 | 0 | 0.00 | 0 | 0 |
| 0 | 0 | 0.00 | 0 | 0 |
| 0 | 0 | 0.00 | 0 | 0 |
| Totals: | 53852 | 1.24 | 87 | 0.80 |

FIGURE 1


Water Surface Elevation - 70th St



17/21

FIGURE 2


Water Surface Elevation - 4th St. Cul de Sac



18/21

FIGURE 3


Flow Rate - 100 yr, 6 hr Storm - 70th St. Intersection



19121

Figure 4


Flow Rate - 100 yr, 6 hr Storm - 4th St. Inlet location



20121

Figure 5

Flow Rate - 100 yr, 6 hr Storm - 4th St. New inlet location



21/12

APPENDIX C

National Flood Hazard Layer FIRMette



Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT


| | |
|-----------------------------|---|
| SPECIAL FLOOD HAZARD AREAS | Without Base Flood Elevation (BFE) Zone A, V, A99 |
| | With BFE or Depth Zone AE, AO, AH, VE, AR |
| | Regulatory Floodway |
| OTHER AREAS OF FLOOD HAZARD | 0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X |
| | Future Conditions 1% Annual Chance Flood Hazard Zone X |
| | Area with Reduced Flood Risk due to Levee. See Notes, Zone X Area with Flood Risk due to Levee Zone D |
| OTHER AREAS | NO SCREEN Area of Minimal Flood Hazard Zone X |
| | Effective LOMRs Area of Undetermined Flood Hazard Zone D |
| GENERAL STRUCTURES | Channel, Culvert, or Storm Sewer |
| | Levee, Dike, or Floodwall |
| OTHER FEATURES | 20.3 Cross Sections with 1% Annual Chance |
| | 17.5 Water Surface Elevation |
| | Coastal Transect |
| | Base Flood Elevation Line (BFE) |
| | Limit of Study |
| OTHER FEATURES | Jurisdiction Boundary |
| | Coastal Transect Baseline |
| | Profile Baseline |
| MAP PANELS | Hydrographic Feature |
| | Digital Data Available |
| | No Digital Data Available |
| MAP PANELS | Unmapped |
| | The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location. |

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 11/7/2018 at 2:11:11 PM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

679_LIBW - South 100YR6HR



GRADING & DRAINAGE LANGUAGE

WARNING AND DISCLAIMER OF LIABILITY

The City's Stormwater and Floodplain Management Ordinance is intended to minimize the occurrence of losses, hazards and conditions adversely affecting the public health, safety and general welfare which might result from flooding. The Stormwater and Floodplain Management Ordinance identifies floodplains, floodways, flood fringes and special flood hazard areas. However, a property outside these areas could be inundated by floods. Also, much of the city is a dynamic flood area; floodways, floodplains, flood fringes and special flood hazard areas may shift from one location to another, over time, due to natural processes.

WARNING AND DISCLAIMER OF LIABILITY

The flood protection provided by the Stormwater and Floodplain Management Ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Floods larger than the base flood can and will occur on rare occasions. Floodwater heights may be increased by constructed or natural causes. The Stormwater and Floodplain Management Ordinance does not create liability on the part of the city, any officer or employee thereof, or the federal, state or county government for any flood damages that result from reliance on the Ordinance or any administrative decision lawfully made thereunder.

Compliance with the Stormwater and Floodplain Management Ordinance does not ensure complete protection from flooding. Flood-related problems such as natural erosion, streambed meander, or constructed obstructions and diversions may occur and have an adverse effect in the event of a flood. You are advised to consult your own engineer or other expert regarding these considerations.

I have read and understand the above.

4-ZN-2018
Plan Check #

Roger Blum
Owner Representative

11-5-2018
Date



Advanced Consulting & Engineering Solutions

PRELIMINARY DRAINAGE REPORT

For

Goldwater Development

Plan # _____
Case # 4-ZN-2018
Q-S # _____

Located in:
70TH & 4TH Street
Scottsdale, Arizona

☒ Accepted
☐ Corrections

C.O.S. CASE NO. 4-ZN-2018

DG 2/5/19
Reviewed By Date

This day of: February 2019

Engineer of Record:
Joseph Hassell P.E.



Ace Job #: 17-096

Prepared By:
Ace Solutions, LLC
609 N Calgary Ct. Ste. 7
Post Falls, ID 83854
208-777-1854

Prepared For:
Goldwater Boulevard, LLC
Robert Ballard
480-203-8661

Contents

| | |
|---|----|
| INTRODUCTION | 4 |
| Previous Drainage Studies or Master Plan | 4 |
| Location | 5 |
| Description of Property | 5 |
| Vicinity Map | 5 |
| General Project Description | 6 |
| Construction schedule | 6 |
| Applicant information | 6 |
| Engineer Information | 6 |
| STORMWATER DESIGN CRITERIA | 6 |
| Regulations: Preliminary Report | 6 |
| Analysis Methods | 7 |
| Hydrologic Criteria | 7 |
| Datum | 10 |
| STORM WATER MANAGEMENT PLAN | 10 |
| General Description | 10 |
| Hydrological Analysis | 11 |
| Hydraulic Analysis and Design | 12 |
| UNDERGROUND STORAGE TANK DESIGN | 13 |
| UNDERGROUND LEVEL DESIGNS | 16 |
| Erosion Control | 16 |
| Stormwater Pollution Prevention- General Permit | 17 |
| CONCLUSIONS | 17 |
| Warning and Disclaimer of Liability | 17 |
| References | 17 |

TABLES

| | |
|--|----|
| Table 1: Rainfall Depths..... | 12 |
| Table 2: Runoff Coefficients | 12 |
| Table 3: USST Summary..... | 12 |
| Table 4: Estimated Tank Drainage Times | 13 |

FIGURES

| | |
|--|----|
| Figure 1: Water Surface Elevation at 70th St. | 8 |
| Figure 2: Water Surface Elevation at 4th St. | 8 |
| Figure 3: Flow rate at 70th St. | 9 |
| Figure 4: Flow Rate at 4th St. | 9 |
| Figure 5: Flow Rate at new inlet..... | 10 |

LIST OF APPENDICES

| |
|---|
| Appendix A: NOAA Atlas 14, Volume 1 - Precipitation Frequency |
| Appendix B: Stormwater Calculations |
| Appendix C: Floodplain data |
| Appendix D: Plans |
| Appendix E: Warning and Disclaimer of Liability |

INTRODUCTION

This Storm Water Management report is being developed at the request of the City of Scottsdale to verify that runoff from the Goldwater Development site property under developed conditions will comply with the City's stormwater ordinance and its Design Standards and Policy Manual (DSPM). Site location is the corner of 70th and Goldwater Blvd. Old Town Scottsdale, Arizona. Total lot area is 1.19 Ac. The lot currently has a city owned 24-inch diameter stormwater drain from the end of 4th street to a storm drain manhole in Goldwater Boulevard.

The storm drain will need to be eliminated at 4th street. The stormwater will be designed to flow above ground along the southern property line. Near the east end of the property, the storm flow from the street will be captured in a new catch basin which will pipe the water back to the existing stormwater outlet located in Goldwater Blvd. The new area of pipe will need a drainage easement of 12 feet wide. We have planned to use 18-inch diameter storm drain piping.

In order to retain the stormwater from the developed site condition, an underground stormwater storage tank will be utilized. Per our calculations, 7750 cubic feet of storage is required. The tank will be located on the east end of the property. Catch basins around the property will drain to the tank location, where there will be an outfall pipe that drains to the city system at the maximum allowed rate of 1 cubic foot per second. The tank will be designed as such that a storm larger than the 100 year, 2-hour storm will result in excess water draining to a drywell on site. Drainage easements will be given where required at the storage tank and piping locations.

This submittal is considered preliminary not for construction. A final plan set and certifications will be submitted at a later date. The final submittal will reflect the current city code requirements.

Previous Drainage Studies or Master Plan

The city of Scottsdale has provided as built drawings of the stormwater system for the area and has notified us of a maximum discharge rate into the existing storm system of 1.0 cfs. The existing lot does not have any existing stormwater storage volume.

Location

The proposed development site contains approximately 1.19 acres located between Goldwater Boulevard and 4th Street, Scottsdale. Access to the property is from 4th Street.

Description of Property

The property is located between Goldwater Boulevard and 4th Street in Old Town Scottsdale, Arizona. Access to the property is from 4th Street. The property is currently undeveloped. All street front improvements are in place. The property owners have requested a 10 foot in width right of way abandonment adjacent to 4th Street. This right of way abandonment is not necessary for the drainage plan, it affects the layout of the building.

The property is currently zoned for commercial development.

This project is not near a floodplain area and there are no visible wetlands in the area. See attached FEMA map in appendix C for Scottsdale community number 045012.

Vicinity Map



General Project Description

The purpose of the proposed development is to construct a new 5 story residential condominium with parking in the basement and ground level. The project will also include grading, curb and gutter, paving, stormwater retention areas utilizing underground storage tanks, landscaping and sidewalks, building, parking, and relocation of the existing stormwater drains, pipes and easements.

Construction schedule

Construction is anticipated to begin in late summer of 2019. Construction will not be phased.

Applicant information

Owner: Goldwater Boulevard LLC

Contact: Bob Ballard

480-203-8661

Scottsdale, Arizona

Engineer Information

ACE Solutions LLC

Project Engineer: Joseph Hassell, PE

609 N. Calgary Ct. Ste. 7

Post Falls, Idaho 83854

Telephone: 208-777-1854

Email: joeh@acesolutions.pro

STORMWATER DESIGN CRITERIA

Regulations: Preliminary Report

City of Scottsdale 2018 DSPM was used for this report. A final report will use the current DSPM.

Analysis Methods

Our hydrological analysis is based on the Rational Method. This method utilizes rainfall frequencies and runoff characteristics from a watershed to predict peak discharges during storm events. This method is suitable for storm analysis on site 160 ac. or less. The storm event for 100-year frequency was analyzed. Storm event data was collected for the NOAA Atlas 14, volume 1 Version 5.0 of Western United States.

The analysis uses sheet flow across the surfaces for pre-developed conditions as well as post-developed conditions. Time of concentration was calculated using the existing and proposed surface runoff coefficients and the length of basin was from the further reaches on site to the average distance to the proposed detention area.


Hydrologic Criteria

At the requirement of the City of Scottsdale DSPM, hydrologic modeling was completed using the 100-year frequency rainfall events as reported in NOAA Atlas 14, Volume 1 Rainfall Frequency Atlas of the Western United States. This data is included in Appendix A. The runoff response from the 6-hour duration storm event was studied to look at historical drainage patterns. These patterns were studied to determine if runoff would enter or leave the property in its pre-development state. The information used was provided by the Lower Indian Bend Wash Area Drainage Master Study (LIBWADMS). Data from the study allows for us to draw a line at certain areas in order to determine the water surface elevation and the flow rates over time after the storm.

Generally, the study confirms the water will flow past the site and not on to the site. Along Goldwater, water will flow away from the property to the North East. Along 70th street, water generally follows the layout of the street. Logically, some water must continue down 4th street. Study shows the water here is lower than the curb height, and with the existing catch basin capturing water at 4th street there should be no water entering the site from the street. A map showing the water flow directions is provided in Appendix C.

Using data from the study, we can determine the water surface elevation at selected points. Our first study location was along 70th street just to the North of the intersection with 4th Street. The following figure shows the results. A full-size version of each of the following figures can be found in Appendix B.


Figure 1: Water Surface Elevation at 70th St.



It was determined that the maximum water surface elevation at this location is 0.53', or just over 6 inches. The curb height at this location is 6 inches, and the water generally runs to the south. Even if the curb were overtopped at this location, the water flow would lead it south along 70th street to the intersection with 4th street, which has more storage capacity for the flows exhibited.

The water surface elevation was also studied at the 4th street Cul-de-Sac. The following figure shows the results.


Figure 2: Water Surface Elevation at 4th St.



The maximum water surface elevation at this location is 0.47', just under 6 inches. With a 6-inch tall curb at this location, overtopping should not be a concern, especially with the existing catch basin in the Cul-de-Sac capturing stormwater into the city system.


We can also use data from the LIBWADMS to determine the flow rate for the 100-year, 6-hour storm. Figure 3 presents the flow rate over time from the same location studied in figure 1.

Figure 3: Flow rate at 70th St.



Using the information shown above, we determined that the maximum flow at 70th street was 54.31 cfs. This flow occurs 4 hours after the storm. Figure 4 presents information from the same location as figure 2.


Figure 4: Flow Rate at 4th St.



Using this information, it was determined that the maximum historical flow at the 4th street culvert inlet is 5.88 cfs. Since we are planning on removing this inlet, we must design for the same flow to be conveyed back to the city system. This calculation is presented in Appendix B, with the result shown on plan page C6 in Appendix D.

We also viewed the flow rate at the location where the new inlet will be placed. Had this rate been higher than shown in figure 4, we would use this higher rate.

Figure 5: Flow Rate at new inlet



The maximum flow at this location is 4.83 cfs. We will use the data from figure 4 to as the baseline for stormwater flows contained by the city system.

Datum

All elevations listed in this report refer to the NAVD-88 GEOID 09 datum. Upon final submittal We will provide equation and location for conversion to the City of Scottsdale datum and local bench mark.

STORM WATER MANAGEMENT PLAN

General Description

All stormwater runoff will be collected and piped to a detention vault which will outfall into the city storm system. The city will only allow 1.0 cfs discharge at any one time. A drywell will also

be designed to contain flows over the 100-year flood and to speed up outflow from the detention vault.

The proposed detention vault will be constructed to discharge runoff from the site at or below the allowed rate of 1.0 cfs, per the DSPM section 4-1.201. All stormwater will be collected and directed into the underground stormwater storage tank (USST). A Drywell is proposed to capture any overflow above the 100-year event. In the USST, two outflow pipes will be placed at minimum. The first will allow outflow to the city system at the proposed 1.0 cfs. This will be designed to always allow outflow as long as there is water in the USST. A second pipe will be designed above the required storage that allows for outflow to the drywell. The drywell will be sized later, but it is assumed that it will handle all the additional water of storms stronger than the 100-year, 2-hour storm.

The underground detention vault must be constructed to comply with the criteria in the 2018 Design Standards and Policy Manual (DSPM), Chapter 4, Section 4-1.202.

There is also a basement level to the building accessible via a ramp down to the level. This must include drains for the inevitable stormwater that will run down the ramp and water that will run off the cars parked there. Our basement level plan is shown on plan page C2 in Appendix D.

An existing 24-inch diameter storm drain line runs through a section of what will become the ramp down to the lower level. This drain line will be removed, and the easement abandoned to allow for the parking ramp installation. In its' place, a scupper will be installed further south to allow for sheet flow of the street stormwater past the sidewalk. A concrete spillway will be installed beneath the sidewalk and to the south of the parking lot allowing the water to flow past the parking lot. From there it will be conveyed in a v-ditch, lined with rip rap to prevent erosion. It will be directed north directly into a new catch basin, where it will be directed to the city system in a new storm drain. This is shown on plan page C6, included in appendix D. Drainage easements will be provided for the new storm drains. Additional drain pipe will need to be installed to re-route the line towards the existing city drain.

A recreational swimming pool is designed to be on site. The design of this pool is by other firms, but the drains and backwash systems must be connected to the sanitary sewer system.

Hydrological Analysis

For sites that have not been previously developed, the standard formula is shown below:

$$V_r = C(R/12)A$$

See City of Scottsdale DSPM for more information regarding this formula.

The provided spread sheet calculates a weighted "C" to apply over the entire site. All stormwater from the 100-year, 2-hour precipitation event must be contained on site.

Additional calculations are shown using data from NOAA Atlas 14, Volume 1 to determine historical flows for 2, 10, 25, and 100-year storms.

Table 1 provided below summarizes the rainfall amounts for each of the analyzed storm events.

Table 1: Rainfall Depths

| Rainfall Duration | 10-Year | 25-Year | 50-Year | 100-Year |
|-------------------|---------|---------|---------|----------|
| 2 Hour | 1.38" | 1.69" | 1.92" | 2.16" |

A weighted C factor has been calculated for each sub-basin based on the existing and developed conditions using coefficients from the DSPM. Table 2 gives runoff coefficients used to calculate the weighted C value for various land usages. We are considering that the current site can be labeled a gravel floodway and shoulder.

Table 2: Runoff Coefficients

| Land Cover | Specific/Composite | Storm Freq. (years) | | |
|---|-------------------------|---------------------|------|------|
| | | 2-25 | 50 | 100 |
| Lawns, golf courses & parks | Specific Surface Values | 0.20 | 0.25 | 0.30 |
| Paved Streets, Parking Lots, roofs, driveways, etc. | Specific Surface Value | 0.90 | 0.93 | 0.95 |
| Apartments & Condominiums | Composite Area Values | 0.76 | 0.83 | 0.94 |
| Gravel Floodways and Shoulders | Specific Surface Values | 0.68 | 0.78 | 0.82 |

Hydraulic Analysis and Design

Retention

Table 3 provided below summarizes the water surface elevations, inflow, outflow, depth and storage required within the proposed USST. The tank will be composed of multiple cells, which when combined hold a minimum of 7750 cf (100 yr.). The outfall weir allows a maximum of 1.0 cfs. Of outfall directly into the city system. Overflow will be directed into an onsite drywell.

Table 3: USST Summary

| Event | Max WSEL (ft.) AVG | Freeboard (ft.) At outfall | Max Q_{in} (cfs) | Max Q_{out} (cfs) | Depth(ft.) | Storage Requirement (cft.) |
|---------|-----------------------|-------------------------------|--------------------|---------------------|------------|----------------------------|
| 10-Year | TBD | 3.62 | 1.26 | 1.0 | 3.88 | 4544 |

| | | | | | | |
|----------|-----|------|------|-----|------|------|
| 25-Year | TBD | 2.74 | 1.54 | 1.0 | 4.76 | 5565 |
| 100-Year | TBD | 0.88 | 2.12 | 1.0 | 6.62 | 7750 |

WSEL= Water Surface Elevation from bottom of vault at outfall location for indicated storm event

Retention will be provided to control developed runoff release to rates as allowed by the city (1.0 cfs). The Existing Conditions have a greater discharge then allowed. Freeboard will be provided during all analyzed storm events. However, if overtopping were to occur, overflow from the detention vault will be piped to an area drywell. Drywell to be sized at a later date.

UNDERGROUND STORAGE TANK DESIGN

According to the above calculations, a minimum of 7750 cubic feet of storage is required in the USST. As shown on plan page C6 in appendix D, we have designed a trapezoidal tank totaling 1170 square feet in surface area. The total tank will be 7.5' deep to allow for sediment buildup. If we design for 7 feet of storage, the tank should be able to hold 8190 cubic feet of water.

In our current design, we must outflow to the city approximately 6.5' below grade. This leaves 1 foot of water in the tank that must be removed.

The outfall pipe to the city system will be placed near the bottom of the tank, approximately 6 inches from the bottom to allow for sediment to settle. An outfall pipe will be placed within 12 inches of the top of the tank which will outflow to the drywell. The basic design is shown on plan page D1 in Appendix D.

Table 4: Estimated Tank Drainage Times

| Outlet Height (from Base) | Outlet Flow rate (cfs) | Volume Drained by outlet (cu. Ft) | Total Drainage Time (hrs.) |
|------------------------------|------------------------|---|-------------------------------|
| 0'-0.5' | 0.1 (drywell) | 1755 | 5 |
| 1.5' | 1.0 (city system) | 6435 | 1.8 |
| 6.5-7.0' (TBD) | TBD | TBD | TBD |

Table 4 shows the estimated time to drain the tank at full capacity. By adding the results of the last column, we can see that the tank will drain in less than 7 hours.

Comparing the data in Table 4 with the historical flows shown in Figure 4, we see after the 100-Year, 2-hour storm, the tank will empty before off-site stormwater is conveyed through the site. The 4-hour delay shown in Figure 4 will help us to make sure that the city stormwater system is not overloaded when dealing with our outflow and the historical outflow.

Per the DSPM Chapter 4, Section 4-1.202 the storage tank must meet the following criteria, with comments following showing how we plan to meet the criteria:

C. GENERAL CRITERIA FOR UNDERGROUND STORMWATER STORAGE SYSTEM DESIGN

1. Underground stormwater storage systems must demonstrate protection of public health, safety, and welfare as established by the SRC and related policies.

The final design will incorporate these aspects.

2. Storage systems must not be located under structures, parking garages, or significant landscaping such as trees or sizable cactus that would preclude access to or replacement of the facilities.

Please see attached plan pages in Appendix D for storage location. The location shown meets these criteria. We have removed the fence previously shown on drawings to accommodate the tank location shown.

3. The owner must dedicate a public drainage easement to the city which meets the standards for all drainage easements.

This will be comped prior to construction completion. The easement is shown on plan page C6 in Appendix D.

4. Design must address:

- a. Water quality protection measures to protect underground and surface water resources to meet applicable water quality standards.
- b. Vector control within storage system.
- c. Redundancy in case of storage system failure, with attention to the possibility of structure or street flooding, sediment accumulation, or storm events that are greater than the 100-year, 2-hour event.
- d. Initial suspended sediment load removal.
- e. At least a 75-year life of entire system, including the lining and coating of the underground storage tank.
- f. Drainage by gravity. Pumped systems will only be considered if no other reasonable alternative exists with dry wells as a preferred alternative if drainage by gravity is not feasible.

These points will be addressed as part of the final design. We anticipate that the storage system will be able to drain to the adjacent drywell and to the city system via the outflow piping. If the structure should become overtopped, overflow will be piped to an adjacent drywell. As shown in previous paragraphs, we cannot empty the tank completely using the city system and will drain the remainder to a drywell. This will be done via gravity.

D. SPECIFIC CRITERIA FOR UNDERGROUND STORMWATER STORAGE DESIGN

1. Outfall—underground storage systems must have some sort of outfall, such as gravity drains or pumps.

See above notes. The structure will outflow via outflow piping.

2. Pipes—underground storage system pipes must have a smooth interior floor. The city's Maricopa Association of Governments (MAG) supplemental standard detail 2554 shall be used to meet the smooth interior floor requirement for the use of corrugated metal pipes in underground stormwater storage facilities.

These types of pipes will be used.

3. Installation—excavation, bedding, and backfill procedures and materials must be in accordance with MAG standards.

These standards will be followed.

4. Access—a minimum of two access points must be provided for each underground storage system unless waived in advance by stormwater staff to enable inspections and access for removal of accumulated sediment and debris. Access must be in accordance with MAG standards and be placed to maximize the ability to maintain the underground system.

The final detention vault design will follow these standards.

E. CRITERIA FOR OPERATIONS, MAINTENANCE AND LIABILITY

1. Operations and maintenance generally—owner must provide:

- a. Maintenance staff with expertise in operating, inspecting, and maintaining an underground stormwater storage system;
- b. An Operations and Maintenance Manual on site for the system that includes:
 - i. a schedule for inspections and maintenance, and
 - ii. provisions for emergency operations due to power failure, pump failure, and clogged outlet structures;
 - iii. A log of the inspections and required maintenance services.

We will insure the owner provides this information.

2. Inspections and maintenance required—In addition to maintenance required by the SRC and other applicable requirements, owner shall:

- a. Inspect system after each storm event of 0.6 inch or more, and semiannually, preferably before summer and winter rains.
- b. Remove accumulated trash and debris from inlet and outlet structures as needed to ensure free flow of stormwater.
- c. Inspect all other elements of the drainage system (pipes, geotextiles, and stone) and repair/replace elements as needed for the storage system to operate at peak efficiency.

The owner will provide this.

3. Signage—before receiving a C of O, the owner must install signs at each end of the underground storage tank that read "Notice—Underground Stormwater Storage Tank." The size, color, and locations of signs are subject to city staff approval.

This will be provided.

4. Ownership Responsibility Statement – The owner shall provide and sign a statement of responsibility for the system stating and acknowledging the owner is responsible for the maintenance, repair, and potential replacement of the system. Prior to final plan approval, the

owner must provide a signed and notarized document to this effect, in a form satisfactory to the City Attorney, for recordation by the city in the Maricopa County Recorder's Office.

This will be provided.

UNDERGROUND LEVEL DESIGNS

The Underground level must be accounted for in the stormwater design. There is one level underground, accessible from a ramp that meets the existing cul-de-sac. An existing storm pipe runs through this area and will have to be moved.

The ramp to the lower level will have a roof over preventing most of the rainwater from running down the ramp. Also, there will be a small rise in elevation from the cul-de-sac trapping water from the street from getting to the ramp. At the top of this rise we will place a grate drain across all lanes of traffic to catch most water that may try to overflow into the basement level.

At the bottom of the ramp a grate drain will be placed across all lanes of traffic. Catch Basins will be placed within the parking area and the parking sloped slightly to drain the water towards the basins. All the water from the drain and from the basins will be conveyed to a sump pump location. From there the water will be pumped up to the surface level where it will drain to the underground storage tank.

Erosion Control

Description

Construction of the project shall include erosion and sediment control. Perimeter erosion controls shall be installed prior to any soil disturbance on site. Interior erosion controls shall be installed after rough grading. The contractor shall install additional erosion control measures as need and shall be responsible for installing and maintaining all erosion control measures. The owner is responsible for erosion control for all contractors working on the site, including minimizing tracking of soil and debris onto adjacent properties and roadways and wind erosion control.

Areas not being developed or planned to be developed for a period of greater than 14 days shall be stabilized to minimize wind and water erosion. This includes periods of winter shut down. Wind erosion protection shall be accomplished by mulching/crimping until 70% vegetation is established. Permanent erosion control shall be achieved by permanent seeding of slopes, disturbed ditch sections and disturbed pond areas. The seed mix shall be a sustainable perennial variety. Further, the contractor is responsible for all clean-up resulting from site erosion and soil tracking. Tracking must be removed by the end of each work day. Erosion control structures shall be in place prior to any land-disturbing activities. Maintaining erosion control structures, site clean-up, and re-evaluation of the erosion plan shall be done on a regular basis, particularly after any storm water event.

See attached development plans for graphical representation of the erosion control plan.

Stormwater Pollution Prevention- General Permit

If the project requires that a General Permit be obtained by the Arizona State Department of Ecology or EPA, an application package with all related and subsequent requirements may be acquired by contacting the Engineer of Record. The forms and requirements outline in the package are also available on the Scottsdale City website.

CONCLUSIONS

Runoff from developed conditions was compared against the runoff rates modeled for existing conditions. The analysis shows that, with the addition of the proposed detention vault, runoff from all analyzed areas under developed conditions, will be retained during the analyzed storm events when compared to existing conditions. The property outfall location will remain the same.

Warning and Disclaimer of Liability

For this preliminary, conceptual, design we have shown that is feasible to control the stormwater runoff on site and meet the city requirements for discharge into their system. We do not recommend the stormwater facilities be built without further engineering and design and full approval from the city.

A signed warning and disclaimer of liability is included in Appendix E

References

The site plan has been analyzed using Atlas 14, volume 1 rainfall rates and soils information provided by onsite inspection. The City of Scottsdale 2018 DSPM has been used for this submittal.

Please feel free to contact Joe Hassell P.E., or Nick Ebner EIT at 208-777-1854 with any questions or comments regarding this SWMP.



NOAA Atlas 14, Volume 1, Version 5
 Location name: Scottsdale, Arizona, USA*
 Latitude: 33.4897°, Longitude: -111.9299°
 Elevation: 1253.07 ft**
 * source: ESRI Maps
 ** source: USGS



POINT PRECIPITATION FREQUENCY ESTIMATES

Sanja Perica, Sarah Dietz, Sarah Heim, Lillian Hiner, Kazungu Maitaria, Deborah Martin, Sandra Pavlovic, Ishani Roy, Carl Trypaluk, Dale Unruh, Fenglin Yan, Michael Yekta, Tan Zhao, Geoffrey Bonnin, Daniel Brewer, Li-Chuan Chen, Tye Parzybok, John Yarchoan

NOAA, National Weather Service, Silver Spring, Maryland

[PF tabular](#) | [PF graphical](#) | [Maps & aeries](#)

PF tabular



| PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches) ¹ | | | | | | | | | | |
|--|-------------------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-----------------------|
| Duration | Average recurrence interval (years) | | | | | | | | | |
| | 1 | 2 | 5 | 10 | 25 | 50 | 100 | 200 | 500 | 1000 |
| 5-min | 0.183 (0.154-0.223) | 0.240 (0.202-0.291) | 0.326 (0.273-0.395) | 0.392 (0.326-0.472) | 0.481 (0.394-0.577) | 0.550 (0.444-0.657) | 0.620 (0.492-0.739) | 0.692 (0.540-0.824) | 0.788 (0.598-0.940) | 0.862 (0.641-1.03) |
| 10-min | 0.279 (0.234-0.339) | 0.364 (0.307-0.443) | 0.495 (0.415-0.600) | 0.596 (0.496-0.719) | 0.732 (0.599-0.878) | 0.837 (0.676-1.00) | 0.944 (0.748-1.12) | 1.05 (0.821-1.25) | 1.20 (0.911-1.43) | 1.31 (0.976-1.57) |
| 15-min | 0.345 (0.290-0.420) | 0.452 (0.381-0.549) | 0.614 (0.514-0.744) | 0.739 (0.614-0.891) | 0.907 (0.743-1.09) | 1.04 (0.838-1.24) | 1.17 (0.928-1.39) | 1.31 (1.02-1.55) | 1.49 (1.13-1.77) | 1.63 (1.21-1.94) |
| 30-min | 0.465 (0.390-0.565) | 0.608 (0.513-0.740) | 0.827 (0.692-1.00) | 0.995 (0.827-1.20) | 1.22 (1.00-1.47) | 1.40 (1.13-1.67) | 1.58 (1.25-1.88) | 1.76 (1.37-2.09) | 2.00 (1.52-2.39) | 2.19 (1.63-2.61) |
| 60-min | 0.575 (0.483-0.700) | 0.753 (0.635-0.915) | 1.02 (0.857-1.24) | 1.23 (1.02-1.49) | 1.51 (1.24-1.82) | 1.73 (1.40-2.07) | 1.95 (1.55-2.32) | 2.18 (1.70-2.59) | 2.48 (1.88-2.95) | 2.71 (2.02-3.24) |
| 2-hr | 0.666 (0.569-0.795) | 0.863 (0.736-1.03) | 1.16 (0.983-1.37) | 1.38 (1.16-1.64) | 1.69 (1.40-1.99) | 1.92 (1.57-2.26) | 2.16 (1.75-2.54) | 2.41 (1.91-2.82) | 2.74 (2.12-3.21) | 2.99 (2.27-3.54) |
| 3-hr | 0.724 (0.614-0.870) | 0.929 (0.793-1.12) | 1.22 (1.04-1.47) | 1.45 (1.22-1.74) | 1.78 (1.47-2.11) | 2.04 (1.66-2.41) | 2.31 (1.85-2.73) | 2.59 (2.04-3.06) | 2.98 (2.28-3.52) | 3.29 (2.46-3.91) |
| 6-hr | 0.873 (0.756-1.03) | 1.11 (0.962-1.30) | 1.42 (1.23-1.66) | 1.67 (1.43-1.95) | 2.01 (1.70-2.33) | 2.28 (1.90-2.63) | 2.56 (2.10-2.95) | 2.84 (2.28-3.28) | 3.23 (2.53-3.74) | 3.53 (2.71-4.11) |
| 12-hr | 0.977 (0.855-1.13) | 1.23 (1.08-1.44) | 1.57 (1.36-1.81) | 1.82 (1.58-2.11) | 2.17 (1.86-2.50) | 2.44 (2.07-2.81) | 2.72 (2.27-3.13) | 3.00 (2.47-3.45) | 3.37 (2.71-3.91) | 3.67 (2.89-4.28) |
| 24-hr | 1.17 (1.05-1.32) | 1.49 (1.33-1.68) | 1.93 (1.72-2.18) | 2.28 (2.02-2.56) | 2.76 (2.43-3.11) | 3.14 (2.75-3.53) | 3.54 (3.08-3.97) | 3.95 (3.41-4.44) | 4.53 (3.86-5.08) | 4.98 (4.20-5.60) |
| 2-day | 1.26 (1.13-1.43) | 1.62 (1.44-1.82) | 2.12 (1.89-2.39) | 2.53 (2.24-2.84) | 3.09 (2.73-3.47) | 3.54 (3.11-3.98) | 4.02 (3.50-4.52) | 4.51 (3.90-5.08) | 5.21 (4.45-5.87) | 5.76 (4.88-6.51) |
| 3-day | 1.34 (1.19-1.51) | 1.71 (1.52-1.93) | 2.25 (2.00-2.53) | 2.69 (2.38-3.02) | 3.30 (2.91-3.70) | 3.79 (3.32-4.25) | 4.32 (3.75-4.84) | 4.87 (4.20-5.47) | 5.64 (4.80-6.34) | 6.26 (5.28-7.06) |
| 4-day | 1.41 (1.25-1.59) | 1.80 (1.60-2.04) | 2.38 (2.11-2.68) | 2.85 (2.52-3.20) | 3.51 (3.08-3.94) | 4.04 (3.53-4.53) | 4.61 (4.00-5.17) | 5.22 (4.49-5.86) | 6.07 (5.16-6.82) | 6.77 (5.69-7.61) |
| 7-day | 1.57 (1.39-1.77) | 2.00 (1.78-2.26) | 2.64 (2.34-2.98) | 3.16 (2.80-3.56) | 3.90 (3.43-4.38) | 4.49 (3.92-5.04) | 5.12 (4.44-5.75) | 5.79 (4.98-6.51) | 6.73 (5.72-7.57) | 7.49 (6.30-8.45) |
| 10-day | 1.70 (1.51-1.92) | 2.18 (1.94-2.45) | 2.87 (2.55-3.23) | 3.44 (3.04-3.86) | 4.22 (3.71-4.73) | 4.85 (4.24-5.43) | 5.52 (4.79-6.18) | 6.22 (5.36-6.98) | 7.21 (6.14-8.08) | 8.00 (6.74-8.99) |
| 20-day | 2.09 (1.87-2.34) | 2.69 (2.40-3.01) | 3.55 (3.17-3.97) | 4.20 (3.74-4.69) | 5.08 (4.50-5.67) | 5.76 (5.08-6.42) | 6.44 (5.65-7.19) | 7.14 (6.23-7.98) | 8.08 (6.99-9.05) | 8.81 (7.56-9.88) |
| 30-day | 2.44 (2.17-2.74) | 3.14 (2.80-3.52) | 4.14 (3.68-4.63) | 4.90 (4.35-5.47) | 5.92 (5.23-6.60) | 6.70 (5.89-7.47) | 7.51 (6.57-8.36) | 8.32 (7.25-9.27) | 9.42 (8.14-10.5) | 10.3 (8.81-11.5) |
| 45-day | 2.83 (2.53-3.16) | 3.64 (3.26-4.07) | 4.80 (4.29-5.36) | 5.66 (5.04-6.32) | 6.78 (6.02-7.57) | 7.63 (6.76-8.52) | 8.49 (7.49-9.49) | 9.35 (8.21-10.5) | 10.5 (9.13-11.8) | 11.3 (9.82-12.7) |
| 60-day | 3.13 (2.81-3.49) | 4.04 (3.63-4.51) | 5.32 (4.76-5.92) | 6.24 (5.58-6.95) | 7.45 (6.64-8.29) | 8.34 (7.41-9.29) | 9.24 (8.17-10.3) | 10.1 (8.91-11.3) | 11.3 (9.87-12.6) | 12.1 (10.6-13.6) |

¹ Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS). Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values. Please refer to NOAA Atlas 14 document for more information.

[Back to Top](#)

PF graphical

PDS-based depth-duration-frequency (DDF) curves
 Latitude: 33.4897°, Longitude: -111.9299°




NOAA Atlas 14, Volume 1, Version 5


Created (GMT): Fri Nov 2 16:49:47 2018

[Back to Top](#)**Maps & aerals**


Small scale terrain



Large scale terrain



Large scale map



Large scale aerial

11/2/2018

Precipitation Frequency Data Server



[Back to Top](#)

[US Department of Commerce](#)
[National Oceanic and Atmospheric Administration](#)
[National Weather Service](#)
[National Water Center](#)
1325 East West Highway
Silver Spring, MD 20910
Questions?: HDSC.Questions@noaa.gov

[Disclaimer](#)

Calculation Description

Objective: Determine the channel design required to convey the 100-year, 6-hour storm flows.

Method of Analysis: Data provided by the Lower Indian Bend Wash Area Drainage Master Study indicated that the maximum flow is 5.88 cfs at the 4th St. Cul-de-sac. We will use hydraulic study and the manning formula to determine flow.

Results:

It was determined that with the constraints given by the site geometry and the City of Scottsdale's requirements, two types of conveyances will work best. The first type will be constrained by the curb of the parking lot and a second curb constructed on the property line. The resulting rectangular shaped ditch will be about 40 inches wide. A shallow V-ditch will be installed after the parking lot to continue conveying water. Both conveyances will be lined with rip-rap to prevent erosion due to the relatively high flows

Conclusion:

The rectangular ditch needs to be 8 inches deep to convey the flow required. We will use a 10-inch-deep ditch in order to better convey flow higher than the maximum required. At the end of the parking lot, a V-ditch will convey the water back to a catch basin where it will flow to the city storm water system. This ditch will be 6 feet wide at the top, and 8 inches deep. It will slope 1% along its length. This will allow for a maximum flow of 6.15 cfs.

Ace Solutions

Open Channel Flow

| Description | Width (ft) | Depth (ft) | Slope (ft/ft) | Entrance Loss coefficient (K _e) | Mannings n | Area(ft ²) | Wetted Perimeter (ft) | Flow (ft ³ /sec) | Velocity (ft/sec) |
|-------------------------|---------------|------------|---------------|--|------------|------------------------|-----------------------------|--------------------------------|----------------------|
| V-Ditch Sheet Flow | 6 | 0.75 | 0.01 | 0 | 0.03 | 2.25 | 6.08 | 6.154 | 2.73 |
| Rectangle Shape at curb | 3.33 | 0.67 | 0.01 | 0 | 0.03 | 2.23 | 4.67 | 7.114 | 3.19 |

2121

Calculation Description

Objective: Determine the historical flow rate for the 2 year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank. Also we plan to use the city's equation to determine the storage required for the 2-year storm. See the last calculation for additional details on the city's equation.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 2-year rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 2-year, 2-hour storm, the pre-developed outflow is 0.73 cfs and post-developed outflow is 0.78 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2.

Using the city equation, we find that 2842 cubic feet of storage is required for the 2-year, 2 hour storm.

The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations.

4/21

Entire building area basin 1

Preliminary

2-Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.68 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 0.86 |
| Pre-Developed Outflow (c.f.s.) | 0.73 |

Developed Condition

| | |
|--------------------------------------|------|
| Design Storm Intensity (2hr) (in/hr) | 0.86 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 2.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.73 |
| Area x "C" | 0.91 |
| Soil infiltration rate (in/hr) | 0.00 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft³) (see below) | #6 V _{out} (ft³) | Required Storage Volume (ft³) |
|---------------------------|--|------------------------------|---------------------------------|---|---------------------------------|--|
| 0 | | | | | | |
| 5 | 300 | 2.88 | 2.61 | 955 | 0 | 955.32 |
| 10 | 600 | 2.18 | 1.98 | 1319 | 0 | 1318.77 |
| 15 | 900 | 1.81 | 1.64 | 1584 | 0 | 1583.73 |
| 20 | 1200 | 1.61 | 1.46 | 1849 | 0 | 1849.17 |
| 25 | 1500 | 1.41 | 1.28 | 2007 | 0 | 2007.22 |
| 30 | 1800 | 1.22 | 1.10 | 2058 | 0 | 2057.87 |
| 35 | 2100 | 1.14 | 1.03 | 2237 | 0 | 2237.18 |
| 40 | 2400 | 1.06 | 0.96 | 2374 | 0 | 2374.50 |
| 45 | 2700 | 0.98 | 0.89 | 2470 | 0 | 2469.81 |
| 50 | 3000 | 0.91 | 0.82 | 2523 | 0 | 2523.13 |
| 55 | 3300 | 0.83 | 0.75 | 2534 | 0 | 2534.45 |
| 60 | 3600 | 0.75 | 0.68 | 2504 | 0 | 2503.78 |
| 120 | 7200 | 0.43 | 0.39 | 2844 | 0 | 2843.83 |

2843.83

$$(1) V_{in} = 1.34 * Q_{dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{dev} * t) + (.34 * Q_{dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.68 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.68 |

CN values not used with the rational method

Post-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.9 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.9 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.2 |
| Gravel | 0.00 | 0.00 | 76 | 0.55 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.73 |

Impervious Area:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation:

$$V_r = C(R/12)A$$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | |
|--|------|
| Pre-Developed Flow (cfs) | 0.73 |
| Post-Developed Flow (cfs) | 0.00 |
| Required Storage Volume (ft ³) | 2842 |
| Storage Volume (ft ³) | 7750 |

} Capacity is Adequate

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

Calculation Description

Objective: Determine the historical flow rate for the 10-year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank. Also we plan to use the city's equation to determine the storage required for the 10-year storm. See the last calculation for additional details on the city's equation.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 10-year rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 10-year, 2-hour storm, the pre-developed outflow is 1.16 cfs and post-developed outflow is 1.26 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2.

Using the city equation, we find that 4544 cubic feet of storage is required for the 10-year, 2 hour storm.

The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations.

Entire building area basin 1

Preliminary

10-Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.68 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 1.38 |
| Pre-Developed Outflow (c.f.s.) | 1.16 |

Developed Condition

| | |
|--------------------------------------|-------|
| Design Storm Intensity (2hr) (in/hr) | 1.38 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 10.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.73 |
| Area x "C" | 0.91 |
| Soil infiltration rate (in/hr) | 0.00 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft ³) (see below) | #6 V _{out} (ft ³) | Required Storage Volume (ft ³) |
|---------------------------|--|------------------------------|---------------------------------|--|--|---|
| 0 | | | | | | |
| 5 | 300 | 4.70 | 4.27 | 1560 | 0 | 1560.35 |
| 10 | 600 | 3.58 | 3.24 | 2159 | 0 | 2159.30 |
| 15 | 900 | 2.96 | 2.68 | 2589 | 0 | 2589.32 |
| 20 | 1200 | 2.63 | 2.39 | 3024 | 0 | 3024.04 |
| 25 | 1500 | 2.31 | 2.10 | 3284 | 0 | 3283.51 |
| 30 | 1800 | 1.99 | 1.81 | 3368 | 0 | 3367.73 |
| 35 | 2100 | 1.86 | 1.69 | 3660 | 0 | 3660.43 |
| 40 | 2400 | 1.74 | 1.58 | 3884 | 0 | 3884.19 |
| 45 | 2700 | 1.61 | 1.46 | 4039 | 0 | 4039.01 |
| 50 | 3000 | 1.48 | 1.35 | 4125 | 0 | 4124.89 |
| 55 | 3300 | 1.36 | 1.23 | 4142 | 0 | 4141.83 |
| 60 | 3600 | 1.23 | 1.12 | 4090 | 0 | 4089.84 |
| 120 | 7200 | 0.69 | 0.63 | 4547 | 0 | 4547.49 |

4547.49

$$(1) V_{in} = 1.34 * Q_{dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{dev} * t) + (.34 * Q_{dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|-------------------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.68 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.68 |

CN values not used with the rational method

Post-Development:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.9 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.9 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.2 |
| Gravel | 0.00 | 0.00 | 76 | 0.55 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.73 |

Impervious Area:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation: $V_r = C(R/12)A$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | | |
|--|------|------------------------|
| Pre-Developed Flow (cfs) | 1.16 | } Capacity is Adequate |
| Post-Developed Flow (cfs) | 0.00 | |
| Required Storage Volume (ft ³) | 4544 | |
| Storage Volume (ft ³) | 7750 | |

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

Calculation Description

Objective: Determine the historical flow rate for the 25 year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank. Also we plan to use the city's equation to determine the storage required for the 25-year storm. See the last calculation for additional details on the city's equation.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 25-year rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 25-year, 2 hour storm, the pre-developed outflow is 1.42 cfs and post-developed outflow is 1.54 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2.

Using the city equation, we find that 5565 cubic feet of storage is required for the 25-year, 2 hour storm.

The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations.

Entire building area basin 1

Preliminary

25-Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.68 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 1.69 |
| Pre-Developed Outflow (c.f.s.) | 1.42 |

Developed Condition

| | |
|--------------------------------------|-------|
| Design Storm Intensity (2hr) (in/hr) | 1.69 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 25.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.73 |
| Area x "C" | 0.91 |
| Soil infiltration rate (in/hr) | 0.04 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft ³) (see below) | #6 V _{out} (ft ³) | Required Storage Volume (ft ³) |
|---------------------------|--|------------------------------|---------------------------------|--|--|---|
| 0 | | | | | | |
| 5 | 300 | 5.77 | 5.24 | 1915 | 0 | 1914.62 |
| 10 | 600 | 4.39 | 3.98 | 2652 | 0 | 2652.03 |
| 15 | 900 | 3.63 | 3.29 | 3178 | 0 | 3177.97 |
| 20 | 1200 | 3.23 | 2.93 | 3711 | 0 | 3710.59 |
| 25 | 1500 | 2.84 | 2.57 | 4028 | 0 | 4027.70 |
| 30 | 1800 | 2.44 | 2.21 | 4129 | 0 | 4129.28 |
| 35 | 2100 | 2.29 | 2.07 | 4489 | 0 | 4488.77 |
| 40 | 2400 | 2.13 | 1.93 | 4764 | 0 | 4763.91 |
| 45 | 2700 | 1.98 | 1.79 | 4955 | 0 | 4954.68 |
| 50 | 3000 | 1.82 | 1.65 | 5061 | 0 | 5061.10 |
| 55 | 3300 | 1.67 | 1.51 | 5083 | 0 | 5083.16 |
| 60 | 3600 | 1.51 | 1.37 | 5021 | 0 | 5020.86 |
| 120 | 7200 | 0.85 | 0.77 | 5569 | 0 | 5569.02 |

5569.02

$$(1) -V_{in} = 1.34 * Q_{dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{dev} * t) + (.34 * Q_{dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|-------------------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.68 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.68 |

CN values not used with the rational method

Post-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.9 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.9 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.2 |
| Gravel | 0.00 | 0.00 | 76 | 0.55 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.73 |

Impervious Area:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation:

$$V_r = C(R/12)A$$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | | |
|--|------|------------------------|
| Pre-Developed Flow (cfs) | 1.42 | } Capacity is Adequate |
| Post-Developed Flow (cfs) | 0.00 | |
| Required Storage Volume (ft ³) | 5565 | |
| Storage Volume (ft ³) | 7750 | |

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

Calculation Description

Objective: Determine the historical flow rate for the 100 year, 2-hour storm event. This information will help determine the flow rate into the stormwater tank.

Method of Analysis: The rational method of calculating stormwater flow.

Results:

Using data from the NOAA website, the depth in inches of the 100-year, rainfall for various timeframes are used to determine the rainfall intensity. These numbers are shown in column #3.

Conclusion:

For the case of the 100-year, 2-hour storm, the pre-developed outflow is 2.19 cfs, with post-development outflow at 2.12 cfs. The post-development number is found by multiplying the result in column #3, 120-minute row by 2. This The following calculation sheet includes other information that is typically of interest but not necessarily needed for these calculations. An interesting conclusion is that using this method, we end up with a similar required storage as the city's equation (see next set of calculations). 7718 cubic feet vs. 7712 cubic feet.

Entire building area basin 1

Preliminary

One Hundred Year Storm Event

Rational Method

Determine historical flows

Pre-Developed Condition

| | |
|--------------------------------|------|
| Area (acres) | 1.24 |
| Pre-Developed "C" Factor | 0.82 |
| Time Increment (min) | 5.00 |
| Design Storm Intensity (in/hr) | 2.16 |
| Pre-Developed Outflow (c.f.s.) | 2.19 |

Developed Condition

| | |
|--------------------------------------|--------|
| Design Storm Intensity (2hr) (in/hr) | 2.16 |
| # of 600 Gallon Dry Wells | 0 |
| # of 1000 Gallon Dry Wells | 0 |
| Post-Developed Outflow (cfs) | 0.00 |
| Design Year Flow (yr) | 100.00 |
| Area (acres) | 1.24 |
| Developed "C" Factor | 0.80 |
| Area x "C" | 0.98 |
| Soil infiltration rate (in/hr) | 0.04 |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

| #1 Time Inc. (min.) | #2 t Time Inc. (sec.) (#1*60) | #3 Intensity (in./hr.) | #4 Q _{dev} (cfs) | #5 V _{in} (1) (ft³) (see below) | #6 V _{out} (ft³) | Required Storage Volume (ft³) |
|---------------------------|--|------------------------------|---------------------------------|---|---------------------------------|--|
| 0 | | | | | | |
| 5 | 300 | 7.44 | 7.32 | 2676 | 0 | 2676.03 |
| 10 | 600 | 5.66 | 5.57 | 3709 | 0 | 3708.53 |
| 15 | 900 | 4.68 | 4.60 | 4445 | 0 | 4445.19 |
| 20 | 1200 | 4.17 | 4.10 | 5195 | 0 | 5195.38 |
| 25 | 1500 | 3.67 | 3.61 | 5647 | 0 | 5646.57 |
| 30 | 1800 | 3.16 | 3.11 | 5799 | 0 | 5798.75 |
| 35 | 2100 | 2.96 | 2.91 | 6302 | 0 | 6301.60 |
| 40 | 2400 | 2.76 | 2.71 | 6685 | 0 | 6685.45 |
| 45 | 2700 | 2.56 | 2.51 | 6950 | 0 | 6950.28 |
| 50 | 3000 | 2.35 | 2.31 | 7096 | 0 | 7096.10 |
| 55 | 3300 | 2.15 | 2.12 | 7123 | 0 | 7122.90 |
| 60 | 3600 | 1.95 | 1.92 | 7031 | 0 | 7030.69 |
| 120 | 7200 | 1.08 | 1.06 | 7718 | 0 | 7718.07 |

$$(1) V_{in} = 1.34 * Q_{Dev} * t \text{ for } t < T_c$$

$$V_{in} = (Q_{Dev} * t) + (.34 * Q_{Dev} * T_c) \text{ for } t > T_c$$

$$Q_{dev} = CIA - Q_{DRYWELL} - Q_{INFILTRATION}$$

Pre-Development:

Tributary Area:

| Description: | Area (ft²) | Area (Ac.) | CN | Runoff Coefficients |
|--------------|------------|------------|----|---------------------|
| Grass | 0.00 | 0.00 | 50 | 0.2 |
| Gravel | 53,852.00 | 1.24 | 76 | 0.82 |
| Pavement | 0.00 | 0.00 | 98 | 0.9 |
| Trees/Brush | 0.00 | 0.00 | 36 | 0.2 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 76 | 0.82 |

CN values not used with the rational method

Post-Development:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2,886.00 | 0.07 | 98 | 0.95 |
| Buildings/atrium | 38,174.00 | 0.88 | 98 | 0.95 |
| Grass/Lawn | 12,792.00 | 0.29 | 50 | 0.3 |
| Gravel | 0.00 | 0.00 | 76 | 0.82 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| 0 | 0.00 | 0.00 | 0 | 0 |
| Totals: | 53,852.00 | 1.24 | 87 | 0.80 |

Impervious Area:
Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) |
|--------------|-------------------------|------------|
| Asphalt | 2,886.00 | 0.07 |
| Buildings | 38,174.00 | 0.88 |
| Grass | 0.00 | 0 |
| Totals: | 43,946.00 | 1.01 |

Storm Attenuation: $V_r = C(R/12)A$

| | |
|--|------|
| Stormwater Detention Basin Area (ft ²) | 775 |
| Detention Basin Depth (ft) | 10 |
| Detention Basin Storage Volume (ft ³) | 7750 |

| | | |
|--|------|------------------------|
| Pre-Developed Flow (cfs) | 2.19 | } Capacity is Adequate |
| Post-Developed Flow (cfs) | 0.00 | |
| Required Storage Volume (ft ³) | 7712 | |
| Storage Volume (ft ³) | 7750 | |

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event

Calculation Description

Objective: Determine the required storage volume for the site

Method of Analysis: Equation provided by the City of Scottsdale Design Standards & Policies Manual (DSPM) Chapter 4, Section 1.201.C.

$$Vr = C \left(\frac{R}{12} \right) A$$

See referenced chapter for definition of terms.

Results:

Using data from the NOAA website, the depth in inches of the 100-year, 2-hour rainfall for this site is 2.16 inches. This is the "R" value. The weighted average runoff coefficient, "C" is found to be 0.80 this is shown in the table "Post-Development Tributary Area". This table also shows the "A" value.

Conclusion:

Using the equation above, we find that 7712 cubic feet of storage area is required. We plan to provide a minimum of 7750 cubic feet of storage. The objective is satisfied.

Entire building area basin 1

Preliminary

One Hundred Year Storm Event

DSPM Chapter 4, Section -1.201.C. Storage facilities volume

Pre-Developed Condition

| | |
|--------------------------------|--------|
| Area (square feet) | 53,852 |
| Pre-Developed "C" Factor | 0.82 |
| Design Storm Intensity (in/hr) | 2.16 |
| Pre-Developed Outflow (c.f.s.) | 2.19 |
| Time Increment (min) | 11.11 |

Developed Condition

| | | |
|--------------------------------|--------|---|
| Time Increment (min) | 2 hr | R |
| Design Storm Intensity (in/hr) | 2.16 | |
| Post-Developed Outflow (cfs) | 0.00 | |
| Design Year Flow (yr) | 100.00 | A |
| Area (sq. ft) | 53,852 | |
| Developed "C" Factor | 0.80 | |
| Soil infiltration rate (in/hr) | 0.00 | C |

Flow Calcs:

| | | |
|----------------------|------|-----|
| Q _{out} | 0.00 | CFS |
| Q _{DRYWELL} | 0.00 | CFS |

Storm Attenuation:

$$V_r = C(R/12)A$$

| | |
|--|------|
| Required Storage Volume (ft ³) | 7712 |
| Storage Volume (ft ³) | 7750 |

} Capacity is Adequate

provide minimum detention vault size to hold 7750 cf for maximum 100 yr storm event


Post-Development:

Tributary Area:

| Description: | Area (ft ²) | Area (Ac.) | CN | Runoff Coefficients |
|------------------|-------------------------|------------|----|---------------------|
| Asphalt Pavement | 2886 | 0.07 | 98 | 0.95 |
| Buildings/atrium | 38174 | 0.88 | 98 | 0.95 |
| Grass/Lawn | 12792 | 0.29 | 50 | 0.3 |
| Gravel | 0 | 0.00 | 76 | 0.82 |
| 0 | 0 | 0.00 | 0 | 0 |
| 0 | 0 | 0.00 | 0 | 0 |
| 0 | 0 | 0.00 | 0 | 0 |
| Totals: | 53852 | 1.24 | 87 | 0.80 |

FIGURE 1


Water Surface Elevation - 70th St



17/21

FIGURE 2


Water Surface Elevation - 4th St. Cul de Sac



18/21

Figure 3


Flow Rate - 100 yr, 6 hr Storm - 70th St. Intersection



19121

Figure 4


Flow Rate - 100 yr, 6 hr Storm - 4th St. Inlet location



20121


Figure 5

Flow Rate - 100 yr, 6 hr Storm - 4th St. New inlet location



2/12

APPENDIX C



GRADING & DRAINAGE LANGUAGE

WARNING AND DISCLAIMER OF LIABILITY

The City's Stormwater and Floodplain Management Ordinance is intended to minimize the occurrence of losses, hazards and conditions adversely affecting the public health, safety and general welfare which might result from flooding. The Stormwater and Floodplain Management Ordinance identifies floodplains, floodways, flood fringes and special flood hazard areas. However, a property outside these areas could be inundated by floods. Also, much of the city is a dynamic flood area; floodways, floodplains, flood fringes and special flood hazard areas may shift from one location to another, over time, due to natural processes.

WARNING AND DISCLAIMER OF LIABILITY

The flood protection provided by the Stormwater and Floodplain Management Ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Floods larger than the base flood can and will occur on rare occasions. Floodwater heights may be increased by constructed or natural causes. The Stormwater and Floodplain Management Ordinance does not create liability on the part of the city, any officer or employee thereof, or the federal, state or county government for any flood damages that result from reliance on the Ordinance or any administrative decision lawfully made thereunder.

Compliance with the Stormwater and Floodplain Management Ordinance does not ensure complete protection from flooding. Flood-related problems such as natural erosion, streambed meander, or constructed obstructions and diversions may occur and have an adverse effect in the event of a flood. You are advised to consult your own engineer or other expert regarding these considerations.

I have read and understand the above.

4-ZN-2018
Plan Check #

Roger Blum
Owner Representative

11-5-2018
Date

***ALTA/NSPS LAND TITLE SURVEY
GOLDWATER BOULEVARD, LLC.***


LOT 1 OF LOLOMA II SUBDIVISION, A SINGLE LOT PROPERTY, LOCATED IN N.W. QUARTER OF THE S.E.
QUARTER OF THE N.E. QUARTER OF SECTION 27, TOWNSHIP 2 NORTH, RANGE 4 EAST, GILA & SALT RIVER B.M.,
CITY OF SCOTTSDALE, MARICOPA COUNTY, ARIZONA

OWNERSHIP INFORMATION

2008 CONDO PROPERTIES, LLC., A TEXAS LIMITED LIABILITY COMPANY.
5718 WESTHEIMER, #2000
HOUSTON, TEXAS, 77057

SITE ADDRESS
























7000 E. 4TH STREET
SCOTTSDALE ARIZONA, 85251




VICINITY MAP

NOT TO SCALE

LEGEND (MAY OR MAY NOT APPLY)

- | | |
|---|--|
|  | FOUND: QTY OF SCOTTSDALE BRASS CAP IN HAND HOLE, OR AS NOTED |
|  | 2" IRON BAR FOUND, WITH TAG/LS#22281 |
|  | PROPERTY BOUNDARY |
|  | RIGHT-OF-WAY |
|  | EASEMENT LINE |
|  | BUILDING SETBACK |
|  | ASPHALT (1/2 WIDTH LOCATED) |
|  | CONCRETE |
|  | FENCE |
|  | OVERHEAD ELECTRIC LINE |
|  | SANITARY SEWER LINE |
|  | WATER LINE |
|  | UTILITY POLE |
|  | GUY ANCHOR |
|  | ELECTRICAL TRANSFORMER |
|  | ELECTRICAL METER |
|  | GAS METER |
|  | STORM DRAIN MANHOLE |
|  | FIRE HYDRANT |
|  | WATER METER |
|  | WATER VALVE |
|  | STREET LIGHT |
|  | SIGN AS NOTED |
| IR. C.B | TRAFFIC SIGNAL CONTROL BOX |
| IR. C.B | IRRIGATION CONTROL BOX. |



BASIS OF BEARING

BASIS OF BEARING FOR THIS SURVEY IS S89°14'18"W ALONG THE SOUTH LINE OF THE N.W 1/4 OF THE S.E 1/4 OF THE N.E. 1/4 OF SECTION 27, AS SHOWN PER R-1.

LEGAL DESCRIPTION

LOT 1, LOLOMA II, ACCORDING TO THE PLAT, BOOK 654, PAGES 17, RECORDS OF MARICOPA COUNTY, ARIZONA.

REFERENCES

R-1 A PROPERTY DIVISION OF LOLOMA II, BY JOHN. R. SNODGRASS, PLS 22281, FILED
IN BOOK 654 OF RECORDS, AT PAGE 17, RECORDS OF MARICOPA COUNTY.

R-2 A SPECIAL WARRANTY DEED, FILED UNDER INSTR. NO.20160464176, RECORDS OF MARICOPA COUNTY.

SURVEYOR'S CERTIFICATE

TO: GOLDWATER BOULEVARD, LLC., AN ARIZONA LIMITED LIABILITY COMPANY, KEYBANK NATIONAL ASSOCIATION, A NATIONAL BANKING ASSOCIATION AND ITS SUCCESSORS AND/OR ASSIGNS, AND COMMONWEALTH LAND TITLE INSURANCE COMPANY:

THIS IS TO CERTIFY THAT THIS MAP OR PLAT AND THE SURVEY ON WHICH IT IS BASED WERE MADE IN ACCORDANCE WITH THE 2016 MINIMUM STANDARD DETAIL REQUIREMENTS FOR ALTA/NSPS LAND TITLE SURVEYS, JOINTLY ESTABLISHED AND ADOPTED BY ALTA AND NSPS, AND INCLUDES ITEMS 6(b), 7(a), 7(b)(1), 8, 9, 10(a), 11, 13, 16, 17, 18 19 OF TABLE A THEREOF. THE FIELD WORK WAS COMPLETED ON 07/23/2017.

DATE OF PLAT OR MAP: 3/19/2018

DATE _____

GENERAL NOTES


1. RECORDED AND UNRECORDED DOCUMENTS, MAPS, DEEDS, PRESCRIPTIONS, VERBAL CONTRACTS AND EASEMENTS MAY EXIST THAT EFFECT THIS SURVEY. WE HAVE SHOWN THOSE CERTAIN EXCEPTIONS FOUND IN THE TITLE COMMITMENT NO. C1802110-340-DL4-BB2, DATED MARCH 1, 2018 @ 5:00 P.M.
2. THE STORM DRAIN EASEMENT INFORMATION SHOWN AND DESCRIBED HEREON WAS OBTAINED FROM A PLAT LOLOMA II, JOHN R. SNODGRASS RLS #22281, A LICENSED SURVEYOR IN THE STATE OF ARIZONA.
3. THIS LOT IS ZONED D/RH-2 DO, BY THE CITY OF SCOTTSDALE.
 - A. BUILDING SETBACK= 14' FROM RIGHT OF WAY OF PUBLIC STREET.
4. GOLDWATER BLVD., 70TH STREET, MARSHALL WAY & 4TH STREET ARE PUBLIC RIGHT-OF-WAY, MAINTAINED BY THE CITY OF SCOTTSDALE.
5. TOTAL AREA OF LOT 1, IS 1.19 ACRES, MORE OR LESS.
6. PROPERTY DIMENSIONS SHOWN HAVE BEEN FIELD VERIFIED.
7. ALL AVAILABLE EVIDENCE INDICATES THAT ALL UTILITIES SERVING THE PROPERTY ENTER THROUGH ADJOINING PUBLIC STREETS AND/OR EASEMENTS OF RECORD.
8. THE SUBJECT PROPERTY DOES NOT LIE WITHIN FLOOD ZONE X AS PLOTTED ON FEMA FIRM MAP 04013C22235L EFFECTIVE OCTOBER 16, 2013.
9. THERE ARE NO VISIBLE ENCROACHMENTS UPON THIS LOT.
10. NO OBSERVED EVIDENCE OF CURRENT EARTH MOVING WORK, BUILDING CONSTRUCTION OR BUILDING ADDITIONS.
11. NO PROPOSED CHANGES TO STREET RIGHT-OF-WAY LINES. NO OBSERVED EVIDENCE OF RECENT STREET OR SIDEWALK CONSTRUCTION OR REPAIRS.
12. NO OBSERVED EVIDENCE OF SITE USE AS A SOLID WASTE DUMP, SUMP OR SANITARY LANDFILL.
13. NO WETLAND AREAS AS DELINEATED BY APPROPRIATE AUTHORITIES.
14. GROUND MEASUREMENTS ARE USED AS THE BASIS FOR LOCATION OF ALL FEATURES OF THE SUBJECT PROPERTY.
15. THERE ARE NO BUILDINGS ON THIS SITE.

SCHEDULE B - SECTION II EXCEPTIONS

NOTE: SEE THAT CERTAIN COMMITMENT FOR TITLE INSURANCE ISSUED BY CHICAGO TITLE INSURANCE COMPANY DATED MARCH 1, 2018 AS COMMITMENT NO. C1802110-340-DL4-BB2, WITH EXCEPTIONS AS FOLLOWS: (WITH LIKE NUMBERING)

1. PROPERTY TAXES, WHICH ARE A LIEN NOT YET DUE AND PAYABLE, INCLUDING ANY ASSESSMENTS COLLECTED WITH TAXES TO BE LIEVED FOR THE YEAR 2018.
2. ANY OUTSTANDING LIABILITIES AND OBLIGATIONS, INCLUDING UNPAID ASSESSMENTS, IMPOSED UPON SAID LAND BY REASON OF: (A) INCLUSION THEREOF WITHIN THE BOUNDARIES OF THE SALT RIVER PROJECT AGRICULTURAL IMPROVEMENT AND POWER DISTRICT; (B) MEMBERSHIP OF THE OWNER THEREOF IN THE SALT RIVER VALLEY WATER USERS' ASSOCIATION, AN ARIZONA CORPORATION AND (C) THE TERMS OF ANY WATER RIGHT APPLICATION MADE UNDER THE RECLAMATION ACT OF THE UNITED STATES FOR THE PURPOSES OF OBTAINING WATER RIGHTS FOR SAID LAND.
3. AN EASEMENT FOR THE PURPOSE SHOWN BELOW AND RIGHTS INCIDENTAL THERETO AS SET FORTH IN A DOCUMENT (*AFFECTS SUBJECT PROPERTY*)
GRANTED TO: CITY OF SCOTTSDALE
PURPOSE: PUBLIC UTILITIES
RECORDING DATE: 05/24/1994
RECORDING NO: 1994-415957
RE-RECORDING DATE: 10/18/1994
RE-RECORDING NO: 1994-748898
(THEREAFTER, THE EFFECT OF RELEASE EASEMENT RECORDED SEPTEMBER 24, 2003 IN RECORDING NO. 2003-1341996.)
4. MATTERS CONTAINED IN THAT CERTAIN DOCUMENT. (DOES NOT AFFECT)
ENTITLED: REDEVELOPMENT AGREEMENT
DATED: 04/17/2002
EXECUTED BY: THE CITY OF SCOTTSDALE AND ARTS DISTRICT GROUP, L.L.C., AN ARIZONA LIMITED LIABILITY COMPANY
RECORDING DATE: 04/26/2002
RECORDING NO: 2002-426830
(THE TERMS AND EFFECT OF REDEVELOPMENT AGREEMENT TERMINATION NOTICE RECORDED NOVEMBER 16, 2010 IN RECORDING NO. 2010-1003679.)

5. EASEMENTS, COVENANTS, CONDITIONS AND RESTRICTIONS AS SET FORTH ON THE PLAT
RECORDED IN BOOK 654 OF MAPS, PAGE 17 OF M.C.R.
RECORDING DATE: 10/01/2003. (AFFECTS SUBJECT PROPERTY)



609 N. Calgary Court, Suite 7,
Post Falls, Idaho 83854
PHONE:(208)773-8370
FAX:(208)777-2128
www.acesolutions.pro



***ALTANSPTS LAND TITLE SURVEY
GOLDWATER BOULEVARD, LLC.
CITY OF SCOTTSDALE, MARICOPA COUNTY, ARIZONA***

[illegible]

ISSUE DATE: 11/9/17
PLOT DATE: 3/21/18
DRAWN BY: AG
CHECKED BY: JEH
DWG FILE: 17096-ALTA
PROJ. # 17-096
SHEET TITLE:
***ALTA/NSPS
SURVEY***


1 of 1

STORMWATER CONTROL PLANS FOR GOLDWATER

A SINGLE LOT PROPERTY, LOCATED IN N.W. QUARTER OF THE S.E. QUARTER OF THE N.E. QUARTER OF SECTION 27, TOWNSHIP 2 NORTH, RANGE 4 EAST, GILA & SALT RIVER B.M., MARICOPA COUNTY, ARIZONA

NOTE:

1. BASEMENT LEVEL SUMP PUMP, POWER SOURCE AND CONTROLS TO BE SIZED BY CONTRACTOR. CONSULT ENGINEER OF RECORD FOR FLOW AND HEAD PRESSURE INFORMATION.
2. STORMWATER CONTROL SHALL BE LOCATED IN AREA PROTECTED WITH EASY ACCESS, CLEARLY MARKED.
3. STORMWATER SUMP PUMP AND VAULT SHALL BE TRAFFIC RATED.
4. STORMWATER SUMP PUMP DRAIN TO SURFACE STORMWATER MANHOLE. SEE SHEET C2 FOR LOCATION.
5. ACCESS APPROACH TO BASEMENT PARKING IS COVERED. ALL STORMWATER IS CAPTURED BY GRATE DRAIN AT RIGHT OF WAY.
6. SEE ARCHITECTURAL PLANS FOR BUILDING ELEVATIONS.




BASEMENT DRAINAGE PLAN

LEGEND

- PROPERTY BOUNDARY
- RIGHT-OF-WAY
- EASEMENT LINE
- BUILDING SETBACK
- ASPHALT
- CONCRETE
- GRAVEL
- MAJOR CONTOUR
- MINOR CONTOUR
- FENCE
- CULVERT
- COMMUNICATIONS LINE
- GAS LINE
- OVERHEAD ELECTRIC LINE
- UNDERGROUND ELECTRIC LINE
- SANITARY SEWER
- STORM DRAIN
- WATERLINE
- UTILITY POLE
- GUY ANCHOR
- CATCH BASIN
- DRY WELL
- SEWER MANHOLE
- STORM DRAIN MANHOLE
- FIRE HYDRANT
- YARD HYDRANT
- VALVE
- WELL
- CONIFEROUS TREE
- DECIDUOUS TREE
- SIGN (AS NOTED)
- STORMWATER SURFACE FLOW DIRECTION

SHEET C1 KEY NOTES

1. INSTALL STANDARD CATCH BASINS, TRAFFIC RATED GRATES.
2. INSTALL 6 INCH SCHEDULE 40 PVC DRAIN PIPE. SEE PLAN FOR SLOPE.
3. INSTALL STANDARD TRAFFIC RATED GRATE DRAIN.
4. INSTALL 4 INCH SCHEDULE 40 PVC DRAIN PIPE.
5. INSTALL 4 FOOT DIAMETER STORM DRAIN MANHOLE WITH TRAFFIC RATED LID FOR SUMP PUMP LOCATION.
6. INSTALL 4 INCH SCHEDULE 80 PVC FOR PRESSURE DRAIN TO GROUND DRAIN SYSTEM. ATTACH TO WALL. SEAL ALL PENETRATIONS.
7. EXISTING FIRE HYDRANT TO BE RELOCATED. CONSULT CITY FOR PREFERRED LOCATION.
8. EXISTING CITY STORM DRAIN AND EASEMENT TO BE ABANDONED AND RELOCATED. SEE SHEET C2.
9. REMOVE EXISTING CURB, GUTTER, SIDEWALK AND DRAIN. REINSTALL STANDARD APPROACH AND UNDER DRAIN.



THE SUBMITTAL IS PRELIMINARY AND NOT FOR CONSTRUCTION. REVIEW COPY ONLY.

BOUNDARY INFO PROVIDED IS FOUND IN BOOK 654, PAGE 17 MARICOPA COUNTY, AZ RECORDS.

NO BOUNDARY SURVEY

PROPERTY LINES SHOWN ARE APPROXIMATE. THIS MAP DOES NOT REPRESENT A BOUNDARY SURVEY BY ACE SOLUTIONS, ENGINEERING AND SURVEYING.

DATUM: NAVD 88 GEOID 09
CONTOUR INTERVAL: 1 FOOT

H-Scale 1" = 30'
11 X 17 SCALE 1" = 60'



609 N. Calgary Court, Suite 7,
Post Falls, Idaho 83854
PHONE: (208) 773-8370
FAX: (208) 777-2128
www.acesolutions.pro



Joseph E. Hassell

STORMWATER CONTROL PLANS FOR GOLDWATER MARICOPA COUNTY, ARIZONA

| REV | DATE | DESCRIPTION |
|-----|--------|---------------------|
| 1 | 7/2/18 | REV STORMWATER NOTE |

ISSUE DATE: 3/8/18
PLOT DATE: 2/4/19
DRAWN BY: RUG
CHECKED BY: JEH
DWG FILE: 17-096-SITE
PROJ. # 17-096

SHEET TITLE:
BASEMENT LEV.
SITE PLAN

C1


A SINGLE LOT PROPERTY, LOCATED IN N.W. QUARTER OF THE S.E. QUARTER OF THE N.E.
QUARTER OF SECTION 27, TOWNSHIP 2 NORTH, RANGE 4 EAST, GILA & SALT RIVER
B.M., MARICOPA COUNTY, ARIZONA

6. SEE SHEET C5 FOR FURTHER STORMWATER NOTES

| | |
|--|---------------------------|
| | PROPERTY BOUNDARY |
| | RIGHT-OF-WAY |
| | EASEMENT LINE |
| | BUILDING SETBACK |
| | ASPHALT |
| | CONCRETE |
| | GRAVEL |
| | MAJOR CONTOUR |
| | MINOR CONTOUR |
| | FENCE |
| | CULVERT |
| | COMMUNICATIONS LINE |
| | GAS LINE |
| | OVERHEAD ELECTRIC LINE |
| | UNDERGROUND ELECTRIC LINE |
| | SANITARY SEWER |
| | STORM DRAIN |
| | WATERLINE |
| | UTILITY POLE |
| | GUY ANCHOR |
| | CATCH BASIN |
| | DRY WELL |
| | SEWER MANHOLE |
| | STORM DRAIN MANHOLE |
| | FIRE HYDRANT |
| | YARD HYDRANT |
| | VALVE |
| | WELL |
| | CONIFEROUS TREE |
| | DECIDUOUS TREE |
| | SIGN (AS NOTED) |
| | PALM TREE |

- ① INSTALL STANDARD CATCH BASINS, TRAFFIC RATED GRATES.
- ② INSTALL 6 INCH SCHEDULE 40 PVC DRAIN PIPE. SEE PLAN FOR SLOPE.
- ③ INSTALL STANDARD TRAFFIC RATED GRATE DRAIN.
- ④ INSTALL STORMWATER VAULT WITH OUTFALL METER.
- ⑤ INSTALL DRYWELL TO BE SIZED AT A LATER DATE.
- ⑥ RELOCATE CITY STORMWATER UNDER CURB DRAIN.
- ⑦ RELOCATE CITY STORMWATER DRAIN PIPE AND MANHOLES AS SHOWN.
- ⑧ INSTALL 18 INCH SCHEDULE 80 PVC STORM DRAIN.
- ⑨ UTILITY EASEMENT TO BE DEDICATED TO CITY.
- ⑩ CONNECT INTO CITY 24 INCH DRAIN PIPE.
- ⑪ STUB 6 INCH SCHEDULE 40 DRAIN PIPE FOR DOWN SPOUT CONNECTION. ACTUAL LOCATION TO BE COORDINATED WITH BUILDING ARCHITECT.
- ⑫ BASEMENT PRESSURE DRAIN PIPE CONNECTION.
- ⑬ GROUND LEVEL PARKING ENTRANCE.
- ⑭ REMOVE EXISTING CURB, GUTTER, SIDEWALK AND DRAIN. REINSTALL STANDARD APPROACH AND UNDER DRAIN.

DATUM: NAVD 88 GEOID 09
CONTOUR INTERVAL: 1 FOOT



**STORMWATER CONTROL
PLAN FOR GOLDWATER
MARICOPA COUNTY, ARIZONA**

[illegible]

| | |
|--------|-------------|
| DATE: | 3/8/18 |
| DATE: | 2/4/19 |
| BY: | RJG |
| ED BY: | JEH |
| FILE: | 17-096-SITE |
| # | 17-096 |

TITLE:
**GROUND LEVEL
E PLAN**


C2

STORMWATER CONTROL PLANS FOR GOLDWATER

A SINGLE LOT PROPERTY, LOCATED IN N.W. QUARTER OF THE S.E. QUARTER OF THE N.E. QUARTER OF SECTION 27, TOWNSHIP 2 NORTH, RANGE 4 EAST, GILA & SALT RIVER B.M., MARICOPA COUNTY, ARIZONA

NOTE:

1. OPEN SPACE SURFACE STORMWATER TO BE GRADED AND COLLECTED IN AREA CATCH BASINS. SEE LANDSCAPE PLAN.
2. BUILDING STORMWATER COLLECTION TO BE DIRECTED INTO SURFACE DRAINAGE SYSTEM PRIOR TO STORMWATER VAULT AND METERED OUTFALL. DOWN SPOUT LOCATION BY OTHERS.
3. INSTALL CONCRETE STORMWATER VAULT TO BE SIZED BY ENGINEER. SEE DETAIL FOR INVERT SIZE, LOCATION AND ELEVATION.
4. BASEMENT STORMWATER SUMP PUMP DRAIN TO SURFACE CONNECTION SURFACE AT STORMWATER MANHOLE.
5. STORMWATER VAULT AND OUTFALL METER TO BE DIRECTED INTO CITY STORMWATER SYSTEM. MAXIMUM OUTFALL FLOW SHALL BE 1.0 CFS AT THIS LOCATION.
6. SEE SHEET C5 FOR ADDITIONAL STORMWATER DESIGN



SITE GRADING PLAN

LEGEND

- PROPERTY BOUNDARY
- RIGHT-OF-WAY
- EASEMENT LINE
- BUILDING SETBACK
- ASPHALT
- CONCRETE
- GRAVEL
- MAJOR CONTOUR
- MINOR CONTOUR
- FENCE
- CULVERT
- COMMUNICATIONS LINE
- GAS LINE
- OVERHEAD ELECTRIC LINE
- UNDERGROUND ELECTRIC LINE
- SANITARY SEWER
- STORM DRAIN
- WATERLINE
- UTILITY POLE
- GUY ANCHOR
- CATCH BASIN
- DRY WELL
- SEWER MANHOLE
- STORM DRAIN MANHOLE
- FIRE HYDRANT
- YARD HYDRANT
- VALVE
- WELL
- CONIFEROUS TREE
- DECIDUOUS TREE
- SIGN (AS NOTED)
- PALM TREE

EROSION CONTROL NOTES

1. REFER TO THE ADEQ CATALOG OF STORM WATER BEST MANAGEMENT PRACTICES FOR CONSTRUCTION AND PERMANENT BMPs RELATING TO SLOPE PROTECTION, EROSION, & REVEGETATION. THE FOLLOWING BMPs FROM THE ABOVE MENTIONED CATALOG ARE HEREBY MADE A PART OF THIS PLAN:
BMP #1: TIMING OF CONSTRUCTION
BMP #2: STAGING AREAS
BMP #3: PRESERVATION OF EXISTING VEGETATION
BMP #6: EROSION PREVENTION ON TEMPORARY OR PRIVATE ROADS
BMP #20: TOP SOILING
BMP #21: SEEDING
BMP #23: PLANTING
2. EXISTING VEGETATION TO REMAIN IN PLACE OR BE SALVAGED IF POSSIBLE TO BE REPLACED AFTER CONSTRUCTION IS COMPLETED. ANY VEGETATION THAT IS REMOVED AND/OR DESTROYED MUST BE REPLACED IN KIND AT THE OWNER'S EXPENSE. HYDROSEED ALL DISTURBED AREA AS SHOWN WITH A NATIVE DRYLAND SEED MIX AT A RATE OF 120 LBS/ACRE. BEFORE ANY FERTILIZER IS APPLIED, A SOIL STUDY/ANALYSIS SHOULD BE PERFORMED TO DETERMINE THE APPROPRIATE QUANTITIES OF FERTILIZER REQUIRED, IF ANY.
3. EROSION CONTROL MEASURES ARE TO REMAIN IN PLACE UNTIL IT IS APPARENT THAT VEGETATION IS WELL ESTABLISHED.

SHEET C3 KEY NOTES

1. INSTALL STANDARD CATCH BASINS, TRAFFIC RATED GRATES.
2. INSTALL 6 INCH SCHEDULE 40 PVC DRAIN PIPE. SEE PLAN FOR SLOPE.
3. INSTALL STANDARD TRAFFIC RATED GRATE DRAIN.
4. INSTALL STORMWATER VAULT WITH OUTFALL METER.
5. INSTALL DRYWELL TO BE SIZED AT A LATER DATE.
6. RELOCATE CITY STORMWATER UNDER CURB DRAIN.
7. RELOCATE CITY STORMWATER DRAIN PIPE AND MANHOLES AS SHOWN.
8. INSTALL 18 INCH SCHEDULE 80 PVC STORM DRAIN.
9. UTILITY EASEMENT TO BE DEDICATED TO CITY.
10. CONNECT INTO CITY 24 INCH DRAIN PIPE.
11. STUB 6 INCH SCHEDULE 40 DRAIN PIPE FOR DOWN SPOUT CONNECTION. ACTUAL LOCATION TO BE COORDINATED WITH BUILDING ARCHITECT.
12. BASEMENT PRESSURE DRAIN PIPE CONNECTION.
13. AREA TO BE GRADED AND PLANTED. SEE LANDSCAPE PLAN.
14. INSTALL ASPHALT PARKING. SEE DETAIL.

NOTES:

1. IT IS THE CONTRACTOR'S RESPONSIBILITY FOR MAINTAINING STABILITY OVER THE ENTIRE AREA AND TO KEEP MUD FROM BEING TRACKED OFF SITE.
2. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY SLOPE STABILITY.
3. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO MAINTAIN RIP RAP, STRAW BALES AND STRAW LINED SLOPES UNTIL HYDROSEEDING TAKES ROOT.
4. SWALE AREA SHALL BE SEEDED TO MAINTAIN GOOD GRASS GROWTH.
5. OPERATION AND MAINTENANCE PLAN
A. INSPECTION FREQUENCY
INSPECTIONS ARE NOTED IN THE STORMWATER NARRATIVE AND IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY ENGINEER WHEN INSPECTIONS ARE NEEDED.
B. RESPONSIBLE PERSON OR ENTITY
THE RESPONSIBILITY OF OPERATION AND MAINTENANCE OF THE BMPs SHALL BE THAT OF THE OWNER AND/OR HIS CONTRACTOR
C. ROUTINE MAINTENANCE REQUIREMENTS
SHALL BE THE RESPONSIBILITY OF THE OWNER.
D. SYSTEM FAILURE
IF THE SYSTEM SHOULD EVER FAIL, IT SHALL BE THE OWNER'S RESPONSIBILITY TO ENSURE REPLACEMENT OR REPAIR OF THE SYSTEM TO GOOD WORKING ORDER.

ASBUILT INFORMATION FOR THE SEWER PLACEMENT IN 4TH STREET:
CITY OF SCOTTSDALE, PUBLIC IMPROVEMENTS, 70TH STREET INTERCEPTOR PROJECT NUMBER V-7501, SHEET 13 OF 19.
CITY OF SCOTTSDALE ENGINEERING DRAWING, DATE 8/8/1980, BY KJ ENGINEERING, ASBUILT SHEET C-1.

INSPECTION REQUIREMENTS

- A DESIGN PROFESSIONAL SHALL MAKE AT LEAST THREE REQUIRED INSPECTIONS DURING THE PROCESS OF THIS PROJECT IN ACCORDANCE WITH CITY CODE. THE MINIMUM REQUIRED INSPECTIONS ARE AS FOLLOWS:
- 1) PRIOR TO EXCAVATION TO VERIFY THAT EROSION CONTROL MEASURES AND BEST MANAGEMENT PRACTICES ARE IN PLACE AND PROPERLY INSTALLED.
 - 2) DURING CONSTRUCTION TO VERIFY EROSION CONTROL MEASURES AND B.M.P.s ARE UTILIZED PROPERLY.
 - 3) AT PROJECT COMPLETION TO VERIFY PERMANENT EROSION CONTROL MEASURES AND B.M.P.s ARE INSTALLED PROPERLY.
- DESIGN PROFESSIONAL SHALL PROVIDE WRITTEN VERIFICATION OF THE INSPECTIONS TO THE CITY BUILDING DEPARTMENT. ADDITIONAL INSPECTIONS MAY BE REQUIRED IF WINTERIZATION OF THE SITE IS REQUIRED. BMPs SHOWN HEREON ARE MINIMUM ONLY.

THE SUBMITTAL IS PRELIMINARY AND NOT FOR CONSTRUCTION. REVIEW COPY ONLY.

BOUNDARY INFO PROVIDED IS FOUND IN BOOK 654, PAGE 17 MARICOPA COUNTY, AZ RECORDS.

NO BOUNDARY SURVEY

PROPERTY LINES SHOWN ARE APPROXIMATE. THIS MAP DOES NOT REPRESENT A BOUNDARY SURVEY BY ACE SOLUTIONS, ENGINEERING AND SURVEYING.

DATUM: NAVD 88 GEOID 09
CONTOUR INTERVAL: 1 FOOT



609 N. Calgary Court, Suite 7,
Post Falls, Idaho 83854
PHONE: (208) 773-8370
FAX: (208) 777-2128
www.acesolutions.pro



SITE IMPROVEMENT PLAN FOR GOLDWATER MARICOPA COUNTY, ARIZONA

| DATE | DESCRIPTION |
|----------|------------------------|
| 12/2/18 | STORMWATER VAULT |
| 12/2/18 | RD SETBACKS, PL |
| 11/27/18 | STORMWATER |
| 12/19/18 | 7TH ST. SEWER LOCATION |


ISSUE DATE: 3/8/18
PLOT DATE: 2/5/19
DRAWN BY: AG
CHECKED BY: JEH
DWG FILE: 17-098-SITE
PROJ # P17-004

SHEET TITLE:
SITE PLAN
SITE GRADING

C3

STORMWATER CONTROL PLANS FOR GOLDWATER

A SINGLE LOT PROPERTY, LOCATED IN N.W. QUARTER OF THE S.E. QUARTER OF THE N.E. QUARTER OF SECTION 27, TOWNSHIP 2 NORTH, RANGE 4 EAST, GILA & SALT RIVER B.M., MARICOPA COUNTY, ARIZONA



ROOF LAYOUT PLAN

- NOTE:
1. ROOF AND DECK STORMWATER COLLECTED THROUGH BUILDING DOWN SPOUTS AND DIRECTED INTO STORMWATER SYSTEM. STORMWATER TO BE DIRECTED INTO STORMWATER VAULT AT GROUND LEVEL. SEE SHEET C2 KEY NOTE 4.
 2. ROOF STORMWATER IS NOT REQUIRED TO BE TREATED PRIOR TO ENTERING THE STORMWATER SYSTEM.
 3. STORMWATER VAULT OUTFALL MAXIMUM FLOW 1.0 CFS. EXCESS FLOWS SHALL BE DIRECTED INTO AREA DRYWELL.
 4. AREA DRYWELL LOCATION SHOWN. DRYWELL SIZING SHALL BE AT A LATER DATE.
 5. ROOF AREA 36408 SF.

LEGEND

| | |
|-----|---------------------------|
| --- | PROPERTY BOUNDARY |
| --- | RIGHT-OF-WAY |
| --- | EASEMENT LINE |
| --- | BUILDING SETBACK |
| --- | ASPHALT |
| --- | CONCRETE |
| --- | GRAVEL |
| --- | MAJOR CONTOUR |
| --- | MINOR CONTOUR |
| --- | FENCE |
| --- | CULVERT |
| --- | COMMUNICATIONS LINE |
| --- | GAS LINE |
| --- | OVERHEAD ELECTRIC LINE |
| --- | UNDERGROUND ELECTRIC LINE |
| --- | SANITARY SEWER |
| --- | STORM DRAIN |
| --- | WATERLINE |
| --- | UTILITY POLE |
| --- | GUY ANCHOR |
| --- | CATCH BASIN |
| --- | DRY WELL |
| --- | SEWER MANHOLE |
| --- | STORM DRAIN MANHOLE |
| --- | FIRE HYDRANT |
| --- | YARD HYDRANT |
| --- | VALVE |
| --- | WELL |
| --- | CONIFEROUS TREE |
| --- | DECIDUOUS TREE |
| --- | SIGN (AS NOTED) |
| --- | PALM TREE |


THE SUBMITTAL IS PRELIMINARY AND NOT FOR CONSTRUCTION. REVIEW COPY ONLY.

BOUNDARY INFO PROVIDED IS FOUND IN BOOK 654, PAGE 17 MARICOPA COUNTY, AZ RECORDS.

NO BOUNDARY SURVEY

PROPERTY LINES SHOWN ARE APPROXIMATE. THIS MAP DOES NOT REPRESENT A BOUNDARY SURVEY BY ACE SOLUTIONS, ENGINEERING AND SURVEYING.

DATUM: NAVD 88 GEOID 09
CONTOUR INTERVAL: 1 FOOT



11 X 17 SCALE 1"=60'

ACE SOLUTIONS
Advanced Consulting and Engineering Solutions
609 N. Callegary Court, Suite 7,
Post Falls, Idaho 83854
PHONE: (208) 773-8370
FAX: (208) 773-2128
www.acesolutions.pro



SITE IMPROVEMENT PLAN FOR GOLDWATER MARICOPA COUNTY, ARIZONA

| DATE | DESCRIPTION |
|--------|------------------|
| 7/2/18 | STORMWATER VAULT |
| 7/2/18 | BLD SETBACKS, PL |


ISSUE DATE: 3/9/18
PLOT DATE: 2/4/19
DRAWN BY: AG
CHECKED BY: JEH
DWG FILE: 17-096-SITE
PROJ. # 17-096








SHEET TITLE:
ROOF PLAN LAYOUT

C4



Q100: 2.12 CF

5






THE SUBMITTAL IS PRELIMINARY AND NOT FOR CONSTRUCTION. REVIEW COPY ONLY.



XCE SOLUTIONS
Advanced Consulting and Engineering Solutions

Post Falls, Idaho 83854
PHONE: (208) 773-8370
FAX: (208) 777-2128
www.acesolutions.pro



**SITE IMPROVEMENT PLAN
FOR GOLDWATER
MARICOPA COUNTY, ARIZONA**

[illegible]


| |
|-------------------|
| DATE: 3/8/18 |
| DATE: 2/5/19 |
| OWN BY: NWE |
| CKED BY: JEH |
| FILE: 17-096-SITE |
| J. # 17-096 |
| ET TITLE: |
| TE DETAILS |

02

THE SUBMITTAL IS PRELIMINARY AND NOT FOR
CONSTRUCTION. REVIEW COPY ONLY.

STORMWATER CONTROL PLANS FOR GOLDWATER

A SINGLE LOT PROPERTY, LOCATED IN N.W. QUARTER OF THE S.E. QUARTER OF THE N.E. QUARTER OF SECTION 27, TOWNSHIP 2 NORTH, RANGE 4 EAST, GILA & SALT RIVER B.M., MARICOPA COUNTY, ARIZONA



- NOTE:
1. OPEN SPACE SURFACE STORMWATER TO BE GRADED AND COLLECTED IN AREA CATCH BASINS. SEE LANDSCAPE PLAN.
 2. BUILDING STORMWATER COLLECTION TO BE DIRECTED INTO SURFACE DRAINAGE SYSTEM PRIOR TO STORMWATER VAULT AND METERED OUTFALL. DOWN SPOUT LOCATION BY OTHERS.
 3. INSTALL CONCRETE STORMWATER VAULT TO BE SIZED BY ENGINEER. SEE DETAIL FOR INVERT SIZE, LOCATION AND ELEVATION.
 4. BASEMENT STORMWATER SUMP PUMP DRAIN TO SURFACE CONNECTION SURFACE AT STORMWATER MANHOLE.
 5. STORMWATER VAULT AND OUTFALL METER TO BE DIRECTED INTO CITY STORMWATER SYSTEM. MAXIMUM OUTFALL FLOW SHALL BE 1.0 CFS AT THIS LOCATION.
 6. SEE SHEET C5 FOR FURTHER STORMWATER NOTES

LEGEND

- PROPERTY BOUNDARY
- RIGHT-OF-WAY
- EASEMENT LINE
- BUILDING SETBACK
- ASPHALT
- CONCRETE
- GRAVEL
- MAJOR CONTOUR
- MINOR CONTOUR
- FENCE
- CULVERT
- COMMUNICATIONS LINE
- GAS LINE
- OVERHEAD ELECTRIC LINE
- UNDERGROUND ELECTRIC LINE
- SANITARY SEWER
- STORM DRAIN
- WATERLINE
- UTILITY POLE
- GUY ANCHOR
- CATCH BASIN
- DRY WELL
- SEWER MANHOLE
- STORM DRAIN MANHOLE
- FIRE HYDRANT
- YARD HYDRANT
- VALVE
- WELL
- CONIFEROUS TREE
- DECIDUOUS TREE
- SIGN (AS NOTED)
- PALM TREE

SURFACE DRAINAGE PLAN

SHEET C2 KEY NOTES

1. INSTALL STANDARD CATCH BASINS, TRAFFIC RATED GRATES.
2. INSTALL 6 INCH SCHEDULE 40 PVC DRAIN PIPE. SEE PLAN FOR SLOPE.
3. INSTALL STANDARD TRAFFIC RATED GRATE DRAIN.
4. INSTALL STORMWATER VAULT WITH OUTFALL METER.
5. INSTALL DRYWELL TO BE SIZED AT A LATER DATE.
6. RELOCATE CITY STORMWATER UNDER CURB DRAIN.
7. RELOCATE CITY STORMWATER DRAIN PIPE AND MANHOLES AS SHOWN.
8. INSTALL 18 INCH SCHEDULE 80 PVC STORM DRAIN.
9. UTILITY EASEMENT TO BE DEDICATED TO CITY.
10. CONNECT INTO CITY 24 INCH DRAIN PIPE.
11. STUB 6 INCH SCHEDULE 40 DRAIN PIPE FOR DOWN SPOUT CONNECTION. ACTUAL LOCATION TO BE COORDINATED WITH BUILDING ARCHITECT.
12. BASEMENT PRESSURE DRAIN PIPE CONNECTION.
13. GROUND LEVEL PARKING ENTRANCE.
14. REMOVE EXISTING CURB, GUTTER, SIDEWALK AND DRAIN. REINSTALL STANDARD APPROACH AND UNDER DRAIN.


THE SUBMITTAL IS PRELIMINARY AND NOT FOR CONSTRUCTION. REVIEW COPY ONLY.

BOUNDARY INFO PROVIDED IS FOUND IN BOOK 654, PAGE 17 MARICOPA COUNTY, AZ RECORDS.

NO BOUNDARY SURVEY

PROPERTY LINES SHOWN ARE APPROXIMATE. THIS MAP DOES NOT REPRESENT A BOUNDARY SURVEY BY ACE SOLUTIONS, ENGINEERING AND SURVEYING.

DATUM: NAVD 88 GEOID 09
CONTOUR INTERVAL: 1 FOOT



| DATE | DESCRIPTION |
|--------|------------------------|
| 7/2/18 | STORMWATER VAULT |
| 7/2/18 | GROUND LEVEL SITE PLAN |

ACE SOLUTIONS
Advanced Consulting and Engineering Solutions
609 N. Calgary Court, Suite 7,
Post Falls, Idaho 83854
PHONE: (208) 773-8370
FAX: (208) 777-2128
www.acesolutions.pro

REGISTERED PROFESSIONAL ENGINEER
31787
JOSEPH E. HASSELL
2/15/19
ARIZONA U.S.A.

STORMWATER CONTROL PLAN FOR GOLDWATER

MARICOPA COUNTY, ARIZONA

PROJECT DESCRIPTION

THIS PROJECT IS TO CONSTRUCT A RESIDENTIAL CONDOMINIUM BUILDING WITH INSIDE PARKING. THE PARKING WILL BE SPLIT FROM A BASEMENT LOCATION AND GROUND LEVEL LOCATION. THE BASEMENT PARKING WILL ENTER FROM THE 4TH STREET CUL DE SAC WHILE THE GROUND LEVEL PARKING WILL ENTER FROM THE NORTH SIDE OF 4TH STREET WEST OF THE CUL DE SAC. BOTH ENTRANCES WILL HAVE STORMWATER GRATE DRAINS NEAR THE PROPERTY LINE TO CONTROL THE FLOW OF STORMWATER AND KEEP IT FROM ENTERING THE RIGHT OF WAY. ALL STORMWATER WILL BE CAPTURED ONSITE AND DIRECTED INTO THE CITY STORMWATER SYSTEM OR ONSITE DRY WELL.

THERE IS AN EXISTING CITY STORMWATER INLET ON THE NORTH SIDE OF THE CUL DE SAC WHICH IS PLANNED TO BE MOVED ALONG WITH THE EXISTING STORMWATER DRAIN PIPE. SEE PLAN.

THE CITY REQUIRES THAT LESS THAN 1.0 CFS OF STORMWATER ENTER THE CITY STORMWATER SYSTEM AT ANY TIME. THE ONSITE STORMWATER WILL BE COLLECTED AND DIRECTED INTO AN UNDERGROUND DETENTION VAULT WHICH WILL BE METERED TO NOT ALLOW MORE THAN 1.0 CFS OUTFALL INTO THE CITY SYSTEM AT ANY TIME. THE EXCESS STORMWATER WILL BE DIRECTED THROUGH A WEIR TO AN ONSITE DRYWELL. THE ONSITE DRYWELL WILL BE SIZED AT A LATER DATE.

THERE IS NO PLANNED STOCK PILE OF SOIL ON THE PROPERTY AND ALL CONSTRUCTION TRAFFIC WILL ENTER THE SITE THROUGH A CONSTRUCTION ENTRANCE. THE CONSTRUCTION ENTRANCE SHALL BE MAINTAINED THROUGHOUT THE CONSTRUCTION PROCESS.

THE PROPERTY PERIMETER SHALL HAVE A SILT FENCE INSTALLED PRIOR TO CONSTRUCTION.

CURRENT SITE CONDITIONS

THE SUBJECT AREA IS COMPRISED OF UNDEVELOPED PROPERTY. THERE IS A STORMWATER SYSTEM CROSSING THE SITE THAT WILL NEED TO BE RE-ROUTED FOR THIS PROJECT.

GENERAL NOTES

1. THE PURPOSE OF THIS PLAN IS TO IDENTIFY SITE DISTURBANCE AND BEST MANAGEMENT PRACTICES FOR THE PROPOSED FILL EXTENSION. THIS FILL AREA IS NOT INTENDED TO BE BUILT ON. THIS PLAN IS BASED UPON INFORMATION PROVIDED BY THE PROJECT OWNER AND A TOPOGRAPHIC INFORMATION PROVIDED BY ACE SOLUTIONS LLC. THE OWNER IS RESPONSIBLE FOR VERIFYING SLOPE STABILITY PRIOR TO CONSTRUCTION. OWNER SHALL CONSULT WITH ENGINEER OF RECORD OF ANY DISCREPANCIES OR INCONSISTENCIES FROM THIS PLAN.

2. GROUNDWATER IS NOT ANTICIPATED ON THIS SITE; HOWEVER, SHOULD GROUNDWATER APPEAR CONTACT THE ENGINEER-OF-RECORD IMMEDIATELY. THIS CONSTRUCTION WILL CROSS AREA DRAINAGE. CONTRACTOR SHALL INSTALL CROSSING DURING LOW OR NO FLOW TIME OF YEAR.

3. WINTERIZATION REQUIREMENTS ARE NOT ANTICIPATED ON THIS SITE. ALL SITE DISTURBANCE ACTIVITIES SHOULD BE COMPLETED DURING THE SPRING AND SUMMER MONTHS; HOWEVER SHOULD WINTERIZATION OF THE SITE BE REQUIRED, PROPER BMP PRACTICES SHALL BE FOLLOWED. CONTRACTOR SHALL NOTIFY THE ENGINEER-OF-RECORD.

4. ANY STOCKPILED DIRT AND/OR OTHER MATERIAL SHALL BE PLACED IN A DESIGNATED STOCKPILE AREA OR BE COMPLETELY REMOVED FROM THE SITE. IT IS ANTICIPATED THAT LESS THAN 120 CY OF TOP SOIL WILL BE MOVED AND/OR STOCKPILED DURING CONSTRUCTION. ANY EXPOSED SOIL SHALL BE RELOCATED ON-SITE TO A LOCATION WHICH MAKES TRANSPORTATION OF SILT AND/OR STORM RUNOFF TO ANY BODY OF WATER IMPOSSIBLE.

5. CONSTRUCTION SCHEDULE: START CONSTRUCTION SUMMER 2019; COMPLETION OF ALL CONSTRUCTION BY OCTOBER 2020 (WEATHER PERMITTING).

6. OPERATION AND MAINTENANCE OF EROSION CONTROL MEASURES SHALL BE BY THE PROJECT OWNER, AND/OR THE CONTRACTOR, WHO SHALL MAKE DAILY INSPECTIONS OF ALL FACILITIES. EROSION CONTROL MEASURES ARE TO REMAIN IN PLACE UNTIL VEGETATION IS WELL ESTABLISHED AND OBSERVED BY THE ENGINEER-OF-RECORD. AT THE END OF EACH WORK DAY, THE SITE SHALL BE INSPECTED TO ENSURE THAT THE NECESSARY EROSION CONTROL MEASURES ARE IN PLACE AND FUNCTIONING PROPERLY.

7. CONSTRUCTION TRAFFIC SHALL ENTER THE PROJECT SITE FROM 4TH STREET. THIS STREET IS TO REMAIN FREE FROM ANY CONSTRUCTION DEBRIS. THIS STREET SHALL BE CLEANED AS NECESSARY TO PREVENT MUD/DEBRIS AND OTHER MATERIALS FROM BECOMING A NUISANCE TO OR OBSTRUCTING DAILY TRAFFIC.

8. PRIOR TO CONSTRUCTION, A START-UP LETTER MUST BE ISSUED TO THE CITY BY THE ENGINEER-OF-RECORD AFTER THE REQUIRED SITE INSPECTION APPROVING THE INSTALLATION OF ANY NOTED BMPs. WORK SHALL NOT COMMENCE UNTIL SAID LETTER HAS BEEN APPROVED BY THE CITY BUILDING AND PLANNING DEPARTMENT.

STORMWATER CONTROL PLANS FOR GOLDWATER

A SINGLE LOT PROPERTY, LOCATED IN N.W. QUARTER OF THE S.E. QUARTER OF THE N.E. QUARTER OF SECTION 27, TOWNSHIP 2 NORTH, RANGE 4 EAST, GILA & SALT RIVER B.M., MARICOPA COUNTY, ARIZONA

SITE INFORMATION

OWNER:
GOLDWATER BOULEVARD LLC
CONTACT: BOB BALLARD
P: 480-203-8661

LEGAL DESCRIPTION:
LOT 1, LOT 2, LOT 3, LOT 4, LOT 5, LOT 6, LOT 7, LOT 8, LOT 9, LOT 10, LOT 11, LOT 12, LOT 13, LOT 14, LOT 15, LOT 16, LOT 17, LOT 18, LOT 19, LOT 20, LOT 21, LOT 22, LOT 23, LOT 24, LOT 25, LOT 26, LOT 27, LOT 28, LOT 29, LOT 30, LOT 31, LOT 32, LOT 33, LOT 34, LOT 35, LOT 36, LOT 37, LOT 38, LOT 39, LOT 40, LOT 41, LOT 42, LOT 43, LOT 44, LOT 45, LOT 46, LOT 47, LOT 48, LOT 49, LOT 50, LOT 51, LOT 52, LOT 53, LOT 54, LOT 55, LOT 56, LOT 57, LOT 58, LOT 59, LOT 60, LOT 61, LOT 62, LOT 63, LOT 64, LOT 65, LOT 66, LOT 67, LOT 68, LOT 69, LOT 70, LOT 71, LOT 72, LOT 73, LOT 74, LOT 75, LOT 76, LOT 77, LOT 78, LOT 79, LOT 80, LOT 81, LOT 82, LOT 83, LOT 84, LOT 85, LOT 86, LOT 87, LOT 88, LOT 89, LOT 90, LOT 91, LOT 92, LOT 93, LOT 94, LOT 95, LOT 96, LOT 97, LOT 98, LOT 99, LOT 100, LOT 101, LOT 102, LOT 103, LOT 104, LOT 105, LOT 106, LOT 107, LOT 108, LOT 109, LOT 110, LOT 111, LOT 112, LOT 113, LOT 114, LOT 115, LOT 116, LOT 117, LOT 118, LOT 119, LOT 120, LOT 121, LOT 122, LOT 123, LOT 124, LOT 125, LOT 126, LOT 127, LOT 128, LOT 129, LOT 130, LOT 131, LOT 132, LOT 133, LOT 134, LOT 135, LOT 136, LOT 137, LOT 138, LOT 139, LOT 140, LOT 141, LOT 142, LOT 143, LOT 144, LOT 145, LOT 146, LOT 147, LOT 148, LOT 149, LOT 150, LOT 151, LOT 152, LOT 153, LOT 154, LOT 155, LOT 156, LOT 157, LOT 158, LOT 159, LOT 160, LOT 161, LOT 162, LOT 163, LOT 164, LOT 165, LOT 166, LOT 167, LOT 168, LOT 169, LOT 170, LOT 171, LOT 172, LOT 173, LOT 174, LOT 175, LOT 176, LOT 177, LOT 178, LOT 179, LOT 180, LOT 181, LOT 182, LOT 183, LOT 184, LOT 185, LOT 186, LOT 187, LOT 188, LOT 189, LOT 190, LOT 191, LOT 192, LOT 193, LOT 194, LOT 195, LOT 196, LOT 197, LOT 198, LOT 199, LOT 200, LOT 201, LOT 202, LOT 203, LOT 204, LOT 205, LOT 206, LOT 207, LOT 208, LOT 209, LOT 210, LOT 211, LOT 212, LOT 213, LOT 214, LOT 215, LOT 216, LOT 217, LOT 218, LOT 219, LOT 220, LOT 221, LOT 222, LOT 223, LOT 224, LOT 225, LOT 226, LOT 227, LOT 228, LOT 229, LOT 230, LOT 231, LOT 232, LOT 233, LOT 234, LOT 235, LOT 236, LOT 237, LOT 238, LOT 239, LOT 240, LOT 241, LOT 242, LOT 243, LOT 244, LOT 245, LOT 246, LOT 247, LOT 248, LOT 249, LOT 250, LOT 251, LOT 252, LOT 253, LOT 254, LOT 255, LOT 256, LOT 257, LOT 258, LOT 259, LOT 260, LOT 261, LOT 262, LOT 263, LOT 264, LOT 265, LOT 266, LOT 267, LOT 268, LOT 269, LOT 270, LOT 271, LOT 272, LOT 273, LOT 274, LOT 275, LOT 276, LOT 277, LOT 278, LOT 279, LOT 280, LOT 281, LOT 282, LOT 283, LOT 284, LOT 285, LOT 286, LOT 287, LOT 288, LOT 289, LOT 290, LOT 291, LOT 292, LOT 293, LOT 294, LOT 295, LOT 296, LOT 297, LOT 298, LOT 299, LOT 300, LOT 301, LOT 302, LOT 303, LOT 304, LOT 305, LOT 306, LOT 307, LOT 308, LOT 309, LOT 310, LOT 311, LOT 312, LOT 313, LOT 314, LOT 315, LOT 316, LOT 317, LOT 318, LOT 319, LOT 320, LOT 321, LOT 322, LOT 323, LOT 324, LOT 325, LOT 326, LOT 327, LOT 328, LOT 329, LOT 330, LOT 331, LOT 332, LOT 333, LOT 334, LOT 335, LOT 336, LOT 337, LOT 338, LOT 339, LOT 340, LOT 341, LOT 342, LOT 343, LOT 344, LOT 345, LOT 346, LOT 347, LOT 348, LOT 349, LOT 350, LOT 351, LOT 352, LOT 353, LOT 354, LOT 355, LOT 356, LOT 357, LOT 358, LOT 359, LOT 360, LOT 361, LOT 362, LOT 363, LOT 364, LOT 365, LOT 366, LOT 367, LOT 368, LOT 369, LOT 370, LOT 371, LOT 372, LOT 373, LOT 374, LOT 375, LOT 376, LOT 377, LOT 378, LOT 379, LOT 380, LOT 381, LOT 382, LOT 383, LOT 384, LOT 385, LOT 386, LOT 387, LOT 388, LOT 389, LOT 390, LOT 391, LOT 392, LOT 393, LOT 394, LOT 395, LOT 396, LOT 397, LOT 398, LOT 399, LOT 400, LOT 401, LOT 402, LOT 403, LOT 404, LOT 405, LOT 406, LOT 407, LOT 408, LOT 409, LOT 410, LOT 411, LOT 412, LOT 413, LOT 414, LOT 415, LOT 416, LOT 417, LOT 418, LOT 419, LOT 420, LOT 421, LOT 422, LOT 423, LOT 424, LOT 425, LOT 426, LOT 427, LOT 428, LOT 429, LOT 430, LOT 431, LOT 432, LOT 433, LOT 434, LOT 435, LOT 436, LOT 437, LOT 438, LOT 439, LOT 440, LOT 441, LOT 442, LOT 443, LOT 444, LOT 445, LOT 446, LOT 447, LOT 448, LOT 449, LOT 450, LOT 451, LOT 452, LOT 453, LOT 454, LOT 455, LOT 456, LOT 457, LOT 458, LOT 459, LOT 460, LOT 461, LOT 462, LOT 463, LOT 464, LOT 465, LOT 466, LOT 467, LOT 468, LOT 469, LOT 470, LOT 471, LOT 472, LOT 473, LOT 474, LOT 475, LOT 476, LOT 477, LOT 478, LOT 479, LOT 480, LOT 481, LOT 482, LOT 483, LOT 484, LOT 485, LOT 486, LOT 487, LOT 488, LOT 489, LOT 490, LOT 491, LOT 492, LOT 493, LOT 494, LOT 495, LOT 496, LOT 497, LOT 498, LOT 499, LOT 500, LOT 501, LOT 502, LOT 503, LOT 504, LOT 505, LOT 506, LOT 507, LOT 508, LOT 509, LOT 510, LOT 511, LOT 512, LOT 513, LOT 514, LOT 515, LOT 516, LOT 517, LOT 518, LOT 519, LOT 520, LOT 521, LOT 522, LOT 523, LOT 524, LOT 525, LOT 526, LOT 527, LOT 528, LOT 529, LOT 530, LOT 531, LOT 532, LOT 533, LOT 534, LOT 535, LOT 536, LOT 537, LOT 538, LOT 539, LOT 540, LOT 541, LOT 542, LOT 543, LOT 544, LOT 545, LOT 546, LOT 547, LOT 548, LOT 549, LOT 550, LOT 551, LOT 552, LOT 553, LOT 554, LOT 555, LOT 556, LOT 557, LOT 558, LOT 559, LOT 560, LOT 561, LOT 562, LOT 563, LOT 564, LOT 565, LOT 566, LOT 567, LOT 568, LOT 569, LOT 570, LOT 571, LOT 572, LOT 573, LOT 574, LOT 575, LOT 576, LOT 577, LOT 578, LOT 579, LOT 580, LOT 581, LOT 582, LOT 583, LOT 584, LOT 585, LOT 586, LOT 587, LOT 588, LOT 589, LOT 590, LOT 591, LOT 592, LOT 593, LOT 594, LOT 595, LOT 596, LOT 597, LOT 598, LOT 599, LOT 600, LOT 601, LOT 602, LOT 603, LOT 604, LOT 605, LOT 606, LOT 607, LOT 608, LOT 609, LOT 610, LOT 611, LOT 612, LOT 613, LOT 614, LOT 615, LOT 616, LOT 617, LOT 618, LOT 619, LOT 620, LOT 621, LOT 622, LOT 623, LOT 624, LOT 625, LOT 626, LOT 627, LOT 628, LOT 629, LOT 630, LOT 631, LOT 632, LOT 633, LOT 634, LOT 635, LOT 636, LOT 637, LOT 638, LOT 639, LOT 640, LOT 641, LOT 642, LOT 643, LOT 644, LOT 645, LOT 646, LOT 647, LOT 648, LOT 649, LOT 650, LOT 651, LOT 652, LOT 653, LOT 654, LOT 655, LOT 656, LOT 657, LOT 658, LOT 659, LOT 660, LOT 661, LOT 662, LOT 663, LOT 664, LOT 665, LOT 666, LOT 667, LOT 668, LOT 669, LOT 670, LOT 671, LOT 672, LOT 673, LOT 674, LOT 675, LOT 676, LOT 677, LOT 678, LOT 679, LOT 680, LOT 681, LOT 682, LOT 683, LOT 684, LOT 685, LOT 686, LOT 687, LOT 688, LOT 689, LOT 690, LOT 691, LOT 692, LOT 693, LOT 694, LOT 695, LOT 696, LOT 697, LOT 698, LOT 699, LOT 700, LOT 701, LOT 702, LOT 703, LOT 704, LOT 705, LOT 706, LOT 707, LOT 708, LOT 709, LOT 710, LOT 711, LOT 712, LOT 713, LOT 714, LOT 715, LOT 716, LOT 717, LOT 718, LOT 719, LOT 720, LOT 721, LOT 722, LOT 723, LOT 724, LOT 725, LOT 726, LOT 727, LOT 728, LOT 729, LOT 730, LOT 731, LOT 732, LOT 733, LOT 734, LOT 735, LOT 736, LOT 737, LOT 738, LOT 739, LOT 740, LOT 741, LOT 742, LOT 743, LOT 744, LOT 745, LOT 746, LOT 747, LOT 748, LOT 749, LOT 750, LOT 751, LOT 752, LOT 753, LOT 754, LOT 755, LOT 756, LOT 757, LOT 758, LOT 759, LOT 760, LOT 761, LOT 762, LOT 763, LOT 764, LOT 765, LOT 766, LOT 767, LOT 768, LOT 769, LOT 770, LOT 771, LOT 772, LOT 773, LOT 774, LOT 775, LOT 776, LOT 777, LOT 778, LOT 779, LOT 780, LOT 781, LOT 782, LOT 783, LOT 784, LOT 785, LOT 786, LOT 787, LOT 788, LOT 789, LOT 790, LOT 791, LOT 792, LOT 793, LOT 794, LOT 795, LOT 796, LOT 797, LOT 798, LOT 799, LOT 800, LOT 801, LOT 802, LOT 803, LOT 804, LOT 805, LOT 806, LOT 807, LOT 808, LOT 809, LOT 810, LOT 811, LOT 812, LOT 813, LOT 814, LOT 815, LOT 816, LOT 817, LOT 818, LOT 819, LOT 820, LOT 821, LOT 822, LOT 823, LOT 824, LOT 825, LOT 826, LOT 827, LOT 828, LOT 829, LOT 830, LOT 831, LOT 832, LOT 833, LOT 834, LOT 835, LOT 836, LOT 837, LOT 838, LOT 839, LOT 840, LOT 841, LOT 842, LOT 843, LOT 844, LOT 845, LOT 846, LOT 847, LOT 848, LOT 849, LOT 850, LOT 851, LOT 852, LOT 853, LOT 854, LOT 855, LOT 856, LOT 857, LOT 858, LOT 859, LOT 860, LOT 861, LOT 862, LOT 863, LOT 864, LOT 865, LOT 866, LOT 867, LOT 868, LOT 869, LOT 870, LOT 871, LOT 872, LOT 873, LOT 874, LOT 875, LOT 876, LOT 877, LOT 878, LOT 879, LOT 880, LOT 881, LOT 882, LOT 883, LOT 884, LOT 885, LOT 886, LOT 887, LOT 888, LOT 889, LOT 890, LOT 891, LOT 892, LOT 893, LOT 894, LOT 895, LOT 896, LOT 897, LOT 898, LOT 899, LOT 900, LOT 901, LOT 902, LOT 903, LOT 904, LOT 905, LOT 906, LOT 907, LOT 908, LOT 909, LOT 910, LOT 911, LOT 912, LOT 913, LOT 914, LOT 915, LOT 916, LOT 917, LOT 918, LOT 919, LOT 920, LOT 921, LOT 922, LOT 923, LOT 924, LOT 925, LOT 926, LOT 927, LOT 928, LOT 929, LOT 930, LOT 931, LOT 932, LOT 933, LOT 934, LOT 935, LOT 936, LOT 937, LOT 938, LOT 939, LOT 940, LOT 941, LOT 942, LOT 943, LOT 944, LOT 945, LOT 946, LOT 947, LOT 948, LOT 949, LOT 950, LOT 951, LOT 952, LOT 953, LOT 954, LOT 955, LOT 956, LOT 957, LOT 958, LOT 959, LOT 960, LOT 961, LOT 962, LOT 963, LOT 964, LOT 965, LOT 966, LOT 967, LOT 968, LOT 969, LOT 970, LOT 971, LOT 972, LOT 973, LOT 974, LOT 975, LOT 976, LOT 977, LOT 978, LOT 979, LOT 980, LOT 981, LOT 982, LOT 983, LOT 984, LOT 985, LOT 986, LOT 987, LOT 988, LOT 989, LOT 990, LOT 991, LOT 992, LOT 993, LOT 994, LOT 995, LOT 996, LOT 997, LOT 998, LOT 999, LOT 1000, LOT 1001, LOT 1002, LOT 1003, LOT 1004, LOT 1005, LOT 1006, LOT 1007, LOT 1008, LOT 1009, LOT 1010, LOT 1011, LOT 1012, LOT 1013, LOT 1014, LOT 1015, LOT 1016, LOT 1017, LOT 1018, LOT 1019, LOT 1020, LOT 1021, LOT 1022, LOT 1023, LOT 1024, LOT 1025, LOT 1026, LOT 1027, LOT 1028, LOT 1029, LOT 1030, LOT 1031, LOT 1032, LOT 1033, LOT 1034, LOT 1035, LOT 1036, LOT 1037, LOT 1038, LOT 1039, LOT 1040, LOT 1041, LOT 1042, LOT 1043, LOT 1044, LOT 1045, LOT 1046, LOT 1047, LOT 1048, LOT 1049, LOT 1050, LOT 1051, LOT 1052, LOT 1053, LOT 1054, LOT 1055, LOT 1056, LOT 1057, LOT 1058, LOT 1059, LOT 1060, LOT 1061, LOT 1062, LOT 1063, LOT 1064, LOT 1065, LOT 1066, LOT 1067, LOT 1068, LOT 1069, LOT 1070, LOT 1071, LOT 1072, LOT 1073, LOT 1074, LOT 1075, LOT 1076, LOT 1077, LOT 1078, LOT 1079, LOT 1080, LOT 1081, LOT 1082, LOT 1083, LOT 1084, LOT 1085, LOT 1086, LOT 1087, LOT 1088, LOT 1089, LOT 1090, LOT 1091, LOT 1092, LOT 1093, LOT 1094, LOT 1095, LOT 1096, LOT 1097, LOT 1098, LOT 1099, LOT 1100, LOT 1101, LOT 1102, LOT 1103, LOT 1104, LOT 1105, LOT 1106, LOT 1107, LOT 1108, LOT 1109, LOT 1110, LOT 1111, LOT 1112, LOT 1113, LOT 1114, LOT 1115, LOT 1116, LOT 1117, LOT 1118, LOT 1119, LOT 1120, LOT 1121, LOT 1122, LOT 1123, LOT 1124, LOT 1125, LOT 1126, LOT 1127, LOT 1128, LOT 1129, LOT 1130, LOT 1131, LOT 1132, LOT 1133, LOT 1134, LOT 1135, LOT 1136, LOT 1137, LOT 1138, LOT 1139, LOT 1140, LOT 1141, LOT 1142, LOT 1143, LOT 1144, LOT 1145, LOT 1146, LOT 1147, LOT 1148, LOT 1149, LOT 1150, LOT 1151, LOT 1152, LOT 1153, LOT 1154, LOT 1155, LOT 1156, LOT 1157, LOT 1158, LOT 1159, LOT 1160, LOT 1161, LOT 1162, LOT 1163, LOT 1164, LOT 1165, LOT 1166, LOT 1167, LOT 1168, LOT 1169, LOT 1170, LOT 1171, LOT 1172, LOT 1173, LOT 1174, LOT 1175, LOT 1176, LOT 1177, LOT 1178, LOT 1179, LOT 1180, LOT 1181, LOT 1182, LOT 1183, LOT 1184, LOT 1185, LOT 1186, LOT 1187, LOT 1188, LOT 1189, LOT 1190, LOT 1191, LOT 1192, LOT 1193, LOT 1194, LOT 1195, LOT 1196, LOT 1197, LOT 1198, LOT 1199, LOT 1200, LOT 1201, LOT 1202, LOT 1203, LOT 1204, LOT 1205, LOT 1206, LOT 1207, LOT 1208, LOT 1209, LOT 1210, LOT 1211, LOT 1212, LOT 1213, LOT 1214, LOT 1215, LOT 1216, LOT 1217, LOT 1218, LOT 1219, LOT 1220, LOT 1221, LOT 1222, LOT 1223, LOT 1224, LOT 1225, LOT 1226, LOT 1227, LOT 1228, LOT 1229, LOT 1230, LOT 1231, LOT 1232, LOT 1233, LOT 1234, LOT 1235, LOT 1236, LOT 1237, LOT 1238, LOT 1239, LOT 1240, LOT 1241, LOT 1242, LOT 1243, LOT 1244, LOT 1245, LOT 1246, LOT 1247, LOT 1248, LOT 1249, LOT 1250, LOT 1251, LOT 1252, LOT 1253, LOT 1254, LOT 1255, LOT 1256, LOT 1257, LOT 1258, LOT 1259, LOT 1260, LOT 1261, LOT 1262, LOT 1263, LOT 1264, LOT 1265, LOT 1266, LOT 1267, LOT 1268, LOT 1269, LOT 1270, LOT 1271, LOT 1272, LOT 1273, LOT 1274, LOT 1275, LOT 1276, LOT 1277, LOT 1278, LOT 1279, LOT 1280, LOT 1281, LOT 1282, LOT 1283, LOT 1284, LOT 1285, LOT 1286, LOT 1287, LOT 1288, LOT 1289, LOT 1290, LOT 1291, LOT 1292, LOT 1293, LOT 1294, LOT 1295, LOT 1296, LOT 1297, LOT 1298, LOT 1299, LOT 1300, LOT 1301, LOT 1302, LOT 1303, LOT 1304, LOT 1305, LOT 1306, LOT 1307, LOT 1308, LOT 1309, LOT 1310, LOT 1311, LOT 1312, LOT 1313, LOT 1314, LOT 1315, LOT 1316, LOT 1317, LOT 1318, LOT 1319, LOT 1320, LOT 1321, LOT 1322, LOT 1323, LOT 1324, LOT 1325, LOT 1326, LOT 1327, LOT 1328, LOT 1329, LOT 1330, LOT 1331, LOT 1332, LOT 1333, LOT 1334, LOT 1335, LOT 1336, LOT 1337, LOT 1338, LOT 1339, LOT 1340, LOT 1341, LOT 1342, LOT 1343, LOT 1344, LOT 1345, LOT 1346, LOT 1347, LOT 1348, LOT 1349, LOT 1350, LOT 1351, LOT 1352, LOT 1353, LOT 1354, LOT 1355, LOT 1356, LOT 1357, LOT 1358, LOT 1359, LOT 1360, LOT 1361, LOT 1362, LOT 1363, LOT 1364, LOT 1365, LOT 1366, LOT 1367, LOT 1368, LOT 1369, LOT 1370, LOT 1371, LOT 1372, LOT 1373, LOT 1374, LOT 1375, LOT 1376, LOT 1377, LOT 1378, LOT 1379, LOT 1380, LOT 1381, LOT 1382, LOT 1383, LOT 1384, LOT 1385, LOT 1386, LOT 1387, LOT 1388, LOT 1389, LOT 1390, LOT 1391, LOT 1392, LOT 1393, LOT 1394, LOT 1395, LOT 1396, LOT 1397, LOT 1398, LOT 1399, LOT 1400, LOT 1401, LOT 1402, LOT 1403, LOT 1404, LOT 1405, LOT 1406, LOT 1407, LOT 1408, LOT 1409, LOT 1410, LOT 1411, LOT 1412, LOT 1413, LOT 1414, LOT 1415, LOT 1416, LOT 1417, LOT 1418, LOT 1419, LOT 1420, LOT 1421, LOT 1422, LOT 1423, LOT 1424, LOT 1425, LOT 1426, LOT 1427, LOT 1428, LOT 1429, LOT 1430, LOT 1431, LOT 1432, LOT 1433, LOT 1434, LOT 1435, LOT 1436, LOT 1437, LOT 1438, LOT 1439, LOT 1440, LOT 1441, LOT 1442, LOT 1443, LOT 1444, LOT 1445, LOT 1446, LOT 1447, LOT 1448, LOT 1449, LOT 1450, LOT 1451, LOT 1452, LOT 1453, LOT 1454, LOT 1455, LOT 1456, LOT 1457, LOT 1458, LOT 1459, LOT 1460, LOT 1461, LOT 1462, LOT 1463, LOT 1464, LOT 1465, LOT 1466, LOT 1467, LOT 1468, LOT 1469, LOT 1470, LOT 1471, LOT 1472, LOT 1473, LOT 1474, LOT 1475, LOT 1476, LOT 1477, LOT 1478, LOT 1479, LOT 1480, LOT 1481, LOT 1482, LOT 1483, LOT 1484, LOT 1485, LOT 1486, LOT 1487, LOT 1488, LOT 1489, LOT 1490, LOT 1491, LOT 1492, LOT 1493, LOT 1494, LOT 1495, LOT 1496, LOT 1497, LOT 1498, LOT 1499, LOT 1500, LOT 1501, LOT 1502, LOT 1503, LOT 1504, LOT 1505, LOT 1506, LOT 1507, LOT 1508, LOT 1509, LOT 1510, LOT 1511, LOT 1512, LOT 1513, LOT 1514, LOT 1515, LOT 1516, LOT 1517, LOT 1518, LOT 1519, LOT 1520, LOT 1521, LOT 1522, LOT 1523, LOT 1524, LOT 1525, LOT 1526, LOT 1527, LOT 1528, LOT 1529, LOT 1530, LOT 1531, LOT 1532, LOT 1533, LOT 1534, LOT 1535, LOT 1536, LOT 1537, LOT 1538, LOT 1539, LOT 1540, LOT 1541, LOT 1542, LOT 1543, LOT 1544, LOT 1545, LOT 1546, LOT 1547, LOT 1548, LOT 1549, LOT 1550, LOT 1551, LOT 1552, LOT 1553, LOT 1554, LOT 1555, LOT 1556, LOT 1557, LOT 1558, LOT 1559, LOT 1560, LOT 1561, LOT 1562, LOT 1563, LOT 1564, LOT 1565, LOT 1566, LOT 1567, LOT 1568, LOT 1569, LOT 1570, LOT 1571, LOT 1572, LOT 1573, LOT 1574, LOT 1575, LOT 1576, LOT 1577, LOT 1578, LOT 1579, LOT 1580, LOT 1581, LOT 1582, LOT 1583, LOT 1584, LOT 1585, LOT 1586, LOT 1587, LOT 1588, LOT 1589, LOT 1590, LOT 1591, LOT 1592, LOT 1593, LOT 1594, LOT 1595, LOT 1596, LOT 1597, LOT 1598, LOT 1599, LOT 1600, LOT 1601, LOT 1602, LOT 1603, LOT 1604, LOT 1605, LOT 1606, LOT 1607, LOT 1608, LOT 1609, LOT 1610, LOT 1611, LOT 1612, LOT 1613, LOT 1614, LOT 1615, LOT 1616, LOT 1617, LOT 1618, LOT 1619, LOT 1620, LOT 1621, LOT 1622, LOT 1623, LOT 1624, LOT 1625, LOT 1626, LOT 1627, LOT 1628, LOT 1629, LOT 1630, LOT 1631, LOT 1632, LOT 1633, LOT 1634, LOT 1635, LOT 1636, LOT 1637, LOT 1638, LOT 1639, LOT 1640, LOT 1641, LOT 1642, LOT 1643, LOT 1644, LOT 1645, LOT 1646, LOT 1647, LOT 1648, LOT